

INNOVA NB ABS



... chemically resistant, for areas with high ceilings of 8 – 12 m.

USE

Closed and non-dismountable light fitting according to the standard ČSN EN 60598-1 part 4 intended for chemically challenging or agricultural premises with incidence of vapours like ammonia, lye, alkaline compounds and hot water (hydrolysis). Thanks to the **Narrow Beam** optics, it is suitable for inside spaces with high ceilings, intended for suspension height from 8 to 12 m, e.g. **inside walls and corridors of high agricultural and industrial buildings, rack aisles in production and storage spaces, farms, stables and laboratories** without explosion hazard. The structural design of the light fitting (IP69) allows even placement in food-processing industry - HACCP.


The light fitting resists dust, humidity and washing with spouting water up to 80 °C. The body and the diffuser made of ABS material have high chemical resistance.

An **external terminal block** makes it easy and quick to connect the supply cable.

Emissions in the environment of use may reduce the usability of the plastics; for more information see page 407.

ADVANTAGES

- Light fitting protection **IP66 / IP69**
- High temperature resistance in a range from $t_a = -25\text{ °C}$ to $t_a = 45\text{ °C}$
- Lifetime: 50 000 hours / L90B10
- Lifetime: 100 000 hours / L80B10
- High chemical resistance
- **Narrow Beam (NB)**, ceiling height 8 to 12 m
- **Variable suspension pitch**; optional installation of light fitting even on an existing structure on which the original light fittings were suspended
- **External terminal block makes it easy to connect the supply cable**
- Optional arrangement of light fittings in line without gaps
- **Fully automatic 100% control of functionality and tightness (leak test) during production**
- Easy cleaning and maintenance without need of replacing the light sources
- Eliminated risk of mechanical and electrostatic damage to LED chips
- Optional throughwiring (up to 5 wires inside the light fitting)
- Optional delivery in dimmable version
- Certificates: **ESĚ, ENEC, CB, DLG, HACCP**




INNOVA NB ABS



TECHNICAL DESCRIPTION

- Light fitting protection: **IP66 / IP69**
- Maximum ambient temperature: **$t_a = 45^\circ\text{C}$**
- Lifetime: 50 000 hours / L90B10
- Lifetime: 100 000 hours / L80B10
- Maximum light fitting efficiency: 151 lm/W
- **CRI > 80: 4000 K** – standard
- CRI > 80: 3000 K, 5000 K, 6500 K – on request
- CRI > 90: 3000 K, 4000 K, 5000 K, 6500 K – on request
- MacAdam = 3 SDCM
- Diffuser: transparent ABS with Fresnel lenses, **Narrow Beam** (high chemical resistance, UV stability)
- Body: dark grey ABS (high chemical resistance, UV stability)
- Snap-in mounting clips: stainless steel
- Ventilation membrane in the base eliminating vacuum and condensate build-up
- 3 or 5-pole **external terminal block**, conductor cross-sectional area: 1.5 or 2.5 mm²
- Fittings may be **lined with zero distance** between them
- Optional constant luminous flux (CLO) in DALI version
- Electric equipment: LED modules, fixed output driver or DALI driver
- The package includes: stainless hooks and stainless brackets
- The values stated for power consumption and luminous flux are in a tolerance of $\pm 7,5\%$



INNOVA NB ABS

Diffuser with Fresnel lenses, Narrow Beam, transparent ABS

Type	1x3P	1x5P	DALI 1x5P	2x3P	2x5P	DALI 2x5P
INNOVA 1.4ft NB ABS 4400/840	31672	31676	31680	31684	31688	31692
INNOVA 1.4ft NB ABS 6400/840	31673	31677	31681	31685	31689	31693
INNOVA 1.5ft NB ABS 5500/840	31674	31678	31682	31686	31690	31694
INNOVA 1.5ft NB ABS 8000/840	31675	31679	31683	31687	31691	31695

Example of type marking: 31681 = INNOVA 1.4ft NB ABS 6400/840 **DALI 1x5P**

LEGEND

- 1x3P** - a version featuring a non-dimmable ballast and a single 3-pole external terminal block
- 1x5P** - a version featuring a non-dimmable ballast and a single 5-pole external terminal block
- DALI 1x5P** - a version featuring a digitally dimmable ballast and a single 5-pole external terminal block
- 2x3P** - a version featuring a non-dimmable ballast, two 3-pole external terminal blocks and 3-wire connecting cables (1F), for continuous row installation
- 2x5P** - a version featuring a non-dimmable ballast, two 5-pole external terminal blocks and 5-wire connecting cables (3F), for continuous row installation
- DALI 2x5P** - a version featuring a digitally dimmable ballast, two 5-pole external terminal blocks and 5-wire connecting cables (DALI 1F), for continuous row installation

Light fitting attachment

- a) Directly to a ceiling or a wall with the use of screws and stainless brackets
- b) Suspension with the use of stainless hooks
- c) Attachment with the use of side hangers to the wall - is not included in accessories




VARIABLE INSTALLATION PITCH



LIGHT FITTING INTERCONNECTION

An external terminal block is used to ensure the supply cable can easily and quickly be connected with no need to open the light fixture.

Interconnection of light fittings without spacing



LIGHT FITTING DETAILED VIEW

INNOVA NB ABS

