



The metal light fitting with satinated tempered safety glass is suitable for environment with hazard of explosion of gases, vapours and dust for zones 1, 21 and 2, 22. It meets the requirements of the European Community Directive No. 2014/34/EU. It is resistant against chemically aggressive environment, therefore it fits for industrial premises like chemical factories, plants for processing of gases and oil, power plants, army facilities, automotive factories, laboratories and other facilities of heavy and mechanical engineering. Also emergency back-up source M1h and M3h.

Certification: AR19ATEX001, AR20ATEX023
 Certification: Ex battery box: AR19ATEX131U

The light fitting is certified for the environment:
 Ⓜ II 2G Ex db mb op is IIC T4 Gb; II 2D Ex tb IIIC T 68°C IP66 Db
 Ⓜ II 2G Ex eb mb op is IIC T4 Gb; II 2D Ex tb IIIC T 68°C IP66 Db

3 power versions

3070 - 12300 lm	4000 K	6000 K
-----------------	--------	--------



MORE INFORMATION



BELTR LED

BELTR LED TUBE

The light fitting is suitable for offices, hallways, school interiors, libraries, lecture rooms, sanitary rooms, hospitals and passenger terminals. Also emergency back-up source M1h.

12 power versions

650 - 8000 lm	3000 K	4000 K
	5000 K	6500 K



MORE INFORMATION



Aluminium LED luminaire for surface mounting with integrated switch in side plastic cover. The luminaire is suitable for bathrooms, kitchen units, wall units, dressing rooms and shop windows.

4 power versions

1100 - 5500 lm	4000 K
----------------	--------



MORE INFORMATION



LYRA is round LED wall and ceiling – mounted fashionable luminaire for every interior. It is perfect solution for residential zones, corridors, lounges, hotels, restaurants and entrance areas.

2 power versions

1500 - 1550 lm	3000 K	4000 K
----------------	--------	--------



MORE INFORMATION



The light fitting is suitable for indoor and outdoor spaces with roof with extreme ambient temperatures from -40°C to +75°C. The light fitting is destined mainly for heating stations, metallurgical lines, glass-works, as well as for freezers, cooling plants and other premises without danger of explosion of gases, dusts and flammable vapors.

6 power versions

4000 - 11000 lm	3000 K	4000 K
	5000 K	



MORE INFORMATION



LINEA

LINEA ROUND

LINEA SQUARE

LINEA family is a perfect lighting solution for office buildings, schools, hospitals, libraries, as well as individual lighting of flat interiors, corridors, sanitary and welfare facilities. Also emergency back-up source M1h and M3h.

11 power versions

1200 - 8800 lm	3000 K	4000 K
	5000 K	6500 K



MORE INFORMATION



Interior light fitting from aluminium profile and PC of diffuser It is suitable for selling premises, offices, corridors, entrance and terminal halls, interiors of schools, lecture rooms and hospitals. The light fitting can be easily connected to different lengths and shapes. Also emergency back-up M1h and M3hAt.

10 power versions

1600 - 11000 lm	3000 K	4000 K
	5000 K	6500 K



MORE INFORMATION



The LED light fitting for public lighting. The luminaire is suitable for roads, residential areas, parking areas and outdoor areas. Choice of 15 optical systems. The luminaire is resistant to dust, moisture and gushing water.

16 power versions

2670 - 15690 lm	2700 K	3000 K
	4000 K	5000 K



MORE INFORMATION



The light fitting is suitable for industrial indoor and outdoor roofed spaces, warehouses, garages, workshops, sports areas, transport terminals, utility structures, agricultural operations and laboratories without a danger of explosion of gas, dust and combustible fumes. Also emergency back-up source M1h and M3h.

18 power versions

2600 - 11000 lm	3000 K	4000 K
	6500 K	



MORE INFORMATION



NAOS

NAOS SQUARE

NAOS MPR

NAOS SQUARE MPR

Body of the lamp is made of painted metal sheet and it is supplemented with acryl diffuser sandblasted on both sides. The light fitting is suitable for offices, hallways, school interiors, libraries, lecture rooms, sanitary rooms, hospitals and passenger terminals. Also emergency back-up source M1h and M3h.

12 power versions

1300 - 8800 lm	3000 K	4000 K
	5000 K	6500 K



MORE INFORMATION



The modern light fixture with a body made of lacquered metal and shiny parabolical louvre is an excellent choice for offices, corridors, indoor school spaces, libraries, auditoriums, hospitals, and departure halls. Glare rating UGR < 19. Also emergency back-up source M1h.

5 power versions

1600 - 8000 lm	3000 K	4000 K
	5000 K	6500 K



MORE INFORMATION



PRIMA LED NM	FUTURA NM	BELTR LED NM	TYLIUS LED
HELIOS LED	PLEXI LED	LOVATO	

Non-maintained emergency luminaires for escape routes are intended by its function and shape primarily for being in a set with permanent light fittings. It is recommended for escape routes of interior industrial rooms, storage halls, sports premises, agricultural buildings and laboratories.



MORE INFORMATION



NANOTTICA ES



NANOTTICA ES	NANOTTICA ES TRS	NANOTTICA ES ABS
NANOTTICA ES WB	NANOTTICA ES TRS WB	
NANOTTICA ES NB	NANOTTICA ES TRS NB	

Compared to the standard version, Nanottica ES PC luminaires boast lower energy consumption and significantly higher luminous efficacy (lm/W). The fitting is an excellent choice for illumination of indoor spaces where workers' visual precision is of paramount importance. These include workshops where fine assembly work is performed as well as craft workshops and visual inspection areas. Ideal luminaire installation height: 3.5 to 8 m.

11 power versions		
1300 - 8000 lm		4000 K



MORE INFORMATION

INNOVA



INNOVA	INNOVA NB	INNOVA WB	INNOVA ABS RED
INNOVA ABS	INNOVA NB ABS	INNOVA WB ABS	INNOVA TRS

Closed and non-dismountable light fitting suitable for indoor and outdoor space (even without shelter), industrial, warehouse and agricultural buildings, sports premises, transport terminals, parking lots and garages, workshops and laboratories without explosion hazard. An external terminal strip makes it easy and quick to connect the supply cable with no need to open the fitting (PLUG and PLAY system).

10 power versions		3000 K	4000 K
2600 - 11000 lm		5000 K	6500 K



MORE INFORMATION

PRIMA LED



PRIMA LED	PRIMA LED ABS	PRIMA LED SNS	PRIMA LED VP
PRIMA LED EX	PRIMA LED CLASS II	PRIMA LED TUBE	PRIMA LED ABS RED

The light fitting is suitable for industrial indoor and outdoor roofed spaces, warehouses, sports areas, workshops, garages, transport terminals, utility structures and laboratories without a danger of explosion of gas, dust and combustible fumes. Also emergency back-up source M1h and M3h.

11 power versions		3000 K	4000 K
1300 - 8000 lm		5000 K	6500 K



MORE INFORMATION

CANOPUS



CANOPUS	CANOPUS HE	CANOPUS MINI
CANOPUS NB	CANOPUS HORTI	CANOPUS NB TR

The light fitting is suitable for large operations with high ceilings, industrial outdoor and indoor roofed spaces, warehouses, workshops, sports areas, transport terminals and utility structures without a danger of explosion of gas, dust and combustible fumes. CANOPUS MINI is suitable for production premises, laboratories, research centers, showrooms and halls. Also emergency back-up source M1hAt and M3hAt.

10 power versions		3000 K	4000 K
22000 - 30000 lm		5000 K	6500 K



MORE INFORMATION

TREVOS, a. s.
Nova Ves 34 — 511 01 Turnov
Czech Republic

More information:



www.trevos.eu

NANOTTICA



NANOTTICA	NANOTTICA NB	NANOTTICA VP
NANOTTICA CLASS II	NANOTTICA SNS	NANOTTICA SNS WB
NANOTTICA MAX	NANOTTICA WB	NANOTTICA TRS

Boasting a low unified glow rating (UGR) due to its patented nano-optics, the fixture enhances visual comfort and performance in the workplace. It is a perfect choice for a range of indoor spaces such as industrial premises, agricultural buildings, warehouses, as well as for sports facilities, transport hubs, car parks and garages, and workshops and laboratories with no explosion hazard. Ideal luminaire installation height: 3.5 to 8 m (NB 7.5 to 12 m, WB 2.5 to 4 m)

11 power versions	3000 K	4000 K
1300 - 8000 lm	5000 K	6500 K



MORE INFORMATION

FUTURA MAX



The light fitting is suitable for indoor and outdoor spaces with roof with extreme ambient temperatures from -40°C to +70°C. The light fitting is destined mainly for heating stations, metallurgical lines, glass-works, as well as for freezers, cooling plants and other premises without danger of explosion of gases, dusts and flammable vapors.

6 power versions		3000 K	4000 K
4000 - 11000 lm		5000 K	6500 K



MORE INFORMATION

PRIMA LED MAX



The light fitting is suitable for indoor and outdoor spaces with roof with extreme ambient temperatures from -40°C to +65°C. The light fitting is destined mainly for heating stations, metallurgical lines, glass-works, as well as for freezers, cooling plants and other premises without danger of explosion of gases, dusts and flammable vapors.

2 power versions		3000 K	4000 K
4000 - 5500 lm		5000 K	6500 K



MORE INFORMATION

CANOPUS MAX



The light fitting is suitable for sizable premises with high ceilings and extern ambient temperatures from -40°C to +60°C. The light fitting is destined mainly for heating stations, metallurgical lines, glass-works, but also for freezers, cooling plants and other premises without danger of explosion of gases, dusts and flammable vapors. Also emergency back-up source M1hAt and M3hAt.

3 power versions		3000 K	4000 K
22000 - 30000 lm		5000 K	6500 K



MORE INFORMATION

NANOTTICA ABS



NANOTTICA ABS	NANOTTICA NB ABS	
NANOTTICA WB ABS	NANOTTICA VP ABS	

The fixture comes in versions with varying beam angles. Customers can choose between a narrow beam (NB) luminaire intended for high ceilings (7.5 to 12 m) and a wide beam option (WB) for low ceilings (2.5 to 4 m) ABS fittings are designed for agricultural buildings and other spaces with chemically aggressive environments due to ammonia, lye or alkali fumes.

11 power versions	3000 K	4000 K
1300 - 8000 lm	5000 K	6500 K



MORE INFORMATION

FUTURA



FUTURA	FUTURA NB	FUTURA MAX	FUTURA ES	FUTURA VP
FUTURA ABS	FUTURA SNS	FUTURA HE	FUTURA CLASS II	FUTURA VP

The light fitting is suitable for industrial indoor and outdoor roofed spaces, warehouses, sports areas, workshops, garages, transport terminals, utility structures and laboratories without a danger of explosion of gas, dust and combustible fumes. Also emergency back-up source M1h and M3h.

11 power versions		3000 K	4000 K
2600 - 16000 lm		5000 K	6500 K



MORE INFORMATION

PRIMA LED EX



The light fitting is suitable for the environment with a danger of explosion of gas, dust and combustible fumes. The light fittings meet the requirements of Government Decree 116/2016 Coll. and European Community Directive No.2014/34/EU. Also emergency back-up source M1h and M3h.

Certification: ATEX AR19ATEX004rev1, CB
Certification: M1h, M3h: ATEX AR19ATEX047

The light fitting is certified for the environment:
© II 3 G Ex ec IIC T6 Gc
© II 3 D Ex tc IIIC T85°C Dc IP66

8 power versions		3000 K	4000 K
3200 - 11000 lm		5000 K	6500 K



MORE INFORMATION

PERUN SLIM




PERUN SLIM	PERUN HORTI
------------	-------------

The light fitting is suitable for industrial indoor and outdoor roofed spaces, warehouses, garages, workshops, sports areas, transport terminals, utility structures, agricultural operations and laboratories without a danger of explosion of gas, dust and combustible fumes. Also emergency back-up source M1h and M3hAt.

11 power versions		3000 K	4000 K
1300 - 8000 lm		5000 K	6500 K



MORE INFORMATION



Full version of catalogues available at www.trevos.eu
Do you want to receive News from TREVOS?
Contact us at marketing@trevos.cz