TREVOS


CODE | EAN


102299 | LUXOR LED 2.4ft 6400/840 DALI | 8596328022999



- Degree of protection: IP40
- Ambient temperature: -25—35 °C
- Impact strength: IK02
- Life time: 50000 hours
- System efficacy: 110 lm/W
- Colour rendering index CRI: 80-89, 4000—4000 K
- Chromaticity tolerance (initial MacAdam): SDCM3
- Cable glands: rubber
- Protection class: I
- Max. number of luminaires per circuit breaker B16: 21
- Max. number of luminaires per circuit breaker C16: 35
- Flickering value Pst LM: 1
- Power factor: 0,95
- Stroboscope effect value SVM: 0,4
- Total harmonic distortion: 10
- Energy efficiency class of the light source: D

- Body: steel sheet, white (RAL 9003)
- Diffuser: glossy parabolic louvre, UGR ‹19
- Reflector: steel sheet, white (RAL 9003)
- Connection: screwless five-pole terminal block
- Light fitting for offices, schools etc. for lighting the workspace with high demand on visual performance pursuant to EN 12461-1
- Optical system with mirrored parabolic louvre without glare, UGR < 19
- Digitally dimmable DALI driver (AC/DC)





Code	Type	Luminous flux of LED modules [lm]	Luminous flux of light fitting: [lm]	Power consumption: [W]	System efficacy: [lm/W]	Net weight: [kg]	A [mm]	D [mm]
102299	LUXOR LED 2.4ft 6400/840 DALI	6240	3990	36,3	110	5,5	1224	1030

The values stated for power consumption and luminous flux are in a tolerance of ± 7.5 %

FEATURES

IP40 | up to ta -25°C | up to ta 35°C | 850°C | LED | WARRANTY 5 | D | 220-240 V 50/60 Hz | DALI | CRI >80 | CCT 4000 K 3 SDCM | L90 B10

CERTIFICATION

CE

DOWNLOAD

INSTALLATION MANUAL | DATA SHEET | CE | LDT DATA

TREVOS

CODE | EAN

102299 | LUXOR LED 2.4ft 6400/840 DALI | 8596328022999







