TREVOS


CODE | EAN


103158 | NANOTTICA 1.2ft ES TRS PC 2200/840 ML 3F | 8596328031588




- Degree of protection: IP66/IP69
- Ambient temperature: -25—45 °C
- Impact strength: IK10
- Life time: 200000 hours / L95 @25°C
- System efficacy: 173 lm/W
- Colour rendering index CRI: 80-89, 4000—4000 K
- Chromaticity tolerance (initial MacAdam): SDCM3
- Cable glands: M20x1.5 thread
- Protection class: I
- Max. number of luminaires per circuit breaker B16: 30
- Max. number of luminaires per circuit breaker C16: 51
- Flickering value Pst LM: 0,091
- Power factor: 0,95
- Stroboscope effect value SVM: 0,013
- Total harmonic distortion: 15
- Energy efficiency class of the light source: B

- Body: Clear PC (high mechanical resistance, UV stability)
- Diffuser: Clear PC with nano-optics (high mechanical resistance, UV stability)
- Reflector: Steel sheet, white (RAL 9003), modified for indirect lighting
- Clips: Polyamide + 15 % fibreglass
- Sealing: Polyurethane (PUR), foam-filled base groove
- Connection: Screwless five-pole terminal block, 5-wire connecting cabling for feed-through installation (1.5 mm2 cross-section, 2.5 mm2 available on demand)
- Absolute control over emitted light thanks to patented nano-optics
- Variable suspension spacing ranging from 110 - 370 mm; enable the light to be installed onto suspension fittings left over from previous lighting
- Basic beam angle: medium beam (MB); optimal mounting height: 3.5 to 8 m
- ON/OFF electronic driver (AC, DC on demand)







Code	Type	Ta Max.: [°C]	Luminous flux of LED modules [lm]	Luminous flux of light fitting: [lm]	Power consumption: [W]	System efficacy: [lm/W]	Net weight: [kg]	A [mm]	D [mm]
103158	NANOTTICA 1.2ft ES TRS PC 2200/840 ML 3F	45	2390	2250	13,0	173	1,1	615	110 - 370

The values stated for power consumption and luminous flux are in a tolerance of ± 7.5 %

FEATURES



CERTIFICATION



DOWNLOAD

INSTALLATION MANUAL | DATA SHEET | CE | ENEC | HACCP | LDT DATA

TREVOS

CODE | EAN

103158 | NANOTTICA 1.2ft ES TRS PC 2200/840 ML 3F | 8596328031588







