



10368


TrEx 2.4ft 12800/840 DIS 1F

8590515103683



- Degree of protection: IP66
- Ambient temperature: -40–55 °C
- Impact strength: IK10
- Life time: 50000 hours
- System efficacy: 140 lm/W
- Cable glands: plastic ATEX M20x1.5, or metal (in INOX design on request)
- Protection class: I
- Max. number of luminaires per circuit breaker B16: 23
- Max. number of luminaires per circuit breaker C16: 39
- Power factor: 0,95
- Energy efficiency class of the light source: D

- Body: steel sheet, white (RAL 9003)
- Diffuser: satin, heat-strengthened safety glass
- Reflector: steel sheet, white (RAL 9003)
- Sealing: glued EPDM
- Connection: ATEX, screwless WAGO, maximum cable cross-section: 4 mm²
- Light fitting certified for environments with potentially explosive atmospheres created by gas, dust or flammable vapours, group II, category 2 (zone 1/21)
- Heat-strengthened safety glass with shatter pursuant to ČSN EN 12150-1
- ON/OFF electronic driver, Ex disconnecter



Code	Type	Ta Max.: [°C]	Luminous flux of LED modules [lm]	Luminous flux of light fitting: [lm]	Power consumption: [W]	Net weight: [kg]	A [mm]	D [mm]
10368	TrEx 2.4ft 12800/840 DIS 1F	55	12800	9400	67	16,4	1300	700

The values stated for power consumption and luminous flux are in a tolerance of ± 7.5 %

FEATURES



CERTIFICATION



DOWNLOAD



