



**104183**


**EVELUX L 96/310/727 DALI CP**

**8596328041839**



- Degree of protection: IP66
- Ambient temperature: -40–45 °C
- Impact strength: IK10
- Life time: 100000 hours
- System efficacy: 151 lm/W
- Colour rendering index CRI: 70-79, 2700–2700 K
- Chromaticity tolerance (initial MacAdam): SDCM4
- Cable glands: PG9 thread
- Protection class: I
- Max. number of luminaires per circuit breaker B16: 8
- Max. number of luminaires per circuit breaker C16: 13
- Power factor: 0,98
- Energy efficiency class of the light source: D

- Body: Aluminium alloy, black grey (RAL 7021)
- Diffuser: Heat-strengthened safety glass
- Connection: Screw terminal block with disconnecter for conductors with maximum cross-section of 4 mm<sup>2</sup>
- Light fitting resistant to dust, humidity and spraying water, suitable for roads, residential areas, parking areas and open spaces
- Light fitting suitable for lighting outdoor sports halls, certified for ball impact safety pursuant to DIN 18032-3
- Wide range of optional versions of the light fitting's optical system for diverse applications
- Digitally dimmable DALI driver (AC/DC)



Code	Type	Ta Max.: [°C]	Luminous flux of LED modules [lm]	Luminous flux of light fitting: [lm]	Power consumption: [W]	System efficacy: [lm/W]	Net weight: [kg]	A [mm]	B [mm]	C [mm]
104183	EVELUX L 96/310/727 DALI CP	45	15900	12400	90,6	151	10,1	870	345	127

The values stated for power consumption and luminous flux are in a tolerance of ± 7.5 %

FEATURES



CERTIFICATION



DOWNLOAD





**104183**

EVELUX L 96/310/727 DALI CP

8596328041839

