



105115 | PRIMA 1.5ft TRS PC 4000/840 DALI

8596328051159



- Degree of protection: IP66/IP69
- Ambient temperature: -25–50 °C
- Impact strength: IK10
- Life time: 50000 hours
- System efficacy: 155 lm/W
- Colour rendering index CRI: 80-89, 4000–4000 K
- Chromaticity tolerance (initial MacAdam): SDCM3
- Cable glands: PG 13.5 thread
- Protection class: I
- Max. number of luminaires per circuit breaker B16: 21
- Max. number of luminaires per circuit breaker C16: 35
- Flickering value Pst LM: 1
- Power factor: 0,95
- Stroboscope effect value SVM: 0,4
- Total harmonic distortion: 10
- Energy efficiency class of the light source: D

- Body: clear PC (high mechanical resistance, UV stability)
- Diffuser: clear PC (high mechanical resistance, UV stability)
- Reflector: steel sheet, white (RAL 9003), modified for indirect lighting
- Clips: polyamide + 15 % fibreglass
- Sealing: polyurethane (PUR), foam-filled base groove
- Connection: screwless five-pole terminal block
- Resistant to dust, humidity and spraying water, the light fitting is suitable for both indoor and outdoor roofed industrial spaces
- Variable suspension spacing ranging from 970 - 1230 mm; enable the light to be installed onto suspension fittings left over from previous lighting
- Optimal mounting height: 3 to 8 m
- Digitally dimmable DALI driver (AC/DC)

| Code                                                                                    | Type                             | Ta Max.: [°C] | Luminous flux of LED modules [lm] | Luminous flux of light fitting: [lm] | Power consumption: [W] | System efficacy: [lm/W] | Net weight: [kg] | A [mm] | D [mm]     |
|-----------------------------------------------------------------------------------------|----------------------------------|---------------|-----------------------------------|--------------------------------------|------------------------|-------------------------|------------------|--------|------------|
| 105115                                                                                  | PRIMA 1.5ft TRS PC 4000/840 DALI | 50            | 3850                              | 3620                                 | 23,3                   | 155                     | 2                | 1450   | 970 - 1230 |
| The values stated for power consumption and luminous flux are in a tolerance of ± 7.5 % |                                  |               |                                   |                                      |                        |                         |                  |        |            |

FEATURES



CERTIFICATION



DOWNLOAD





105115 | PRIMA 1.5ft TRS PC 4000/840 DALI

8596328051159

