TREVOS


CODE | EAN


105953 | PRIMA 1.4ft VP ABS 3200/840 | 8596328059537




- Degree of protection: IP66/IP69
- Ambient temperature: -25—50 °C
- Impact strength: IK06
- Life time: 150000 hours / L95 @25°C
- System efficacy: 151 lm/W
- Colour rendering index CRI: 80-89, 4000—4000 K
- Chromaticity tolerance (initial MacAdam): SDCM3
- Cable glands: M20x1.5 thread
- Protection class: I
- Max. number of luminaires per circuit breaker B16: 30
- Max. number of luminaires per circuit breaker C16: 51
- Flickering value Pst LM: 0,076
- Power factor: 0,95
- Stroboscope effect value SVM: 0,022
- Total harmonic distortion: 15
- Energy efficiency class of the light source: C

- Body: Dark grey ABS (high chemical resistance, UV stability, RAL 7001)
- Diffuser: Translucent acrylic (AC), UV stable, chemically resistant
- Reflector: Steel sheet, white (RAL 9003)
- Clips: Polyamide + 15 % fibreglass
- Sealing: Polyurethane (PUR), foam-filled base groove
- Connection: Screwless three-pole terminal block
- Resistant to dust, humidity and spraying water, the light fitting is suitable for both indoor and outdoor roofed industrial spaces
- Variable suspension spacing ranging from 700 - 960 mm; enable the light to be installed onto suspension fittings left over from previous lighting
- Optimal mounting height: 3 to 8 m
- ON/OFF electronic driver (AC, DC on demand)







Code	Type	Ta Max.: [°C]	Luminous flux of LED modules [lm]	Luminous flux of light fitting: [lm]	Power consumption: [W]	System efficacy: [lm/W]	Net weight: [kg]	A [mm]	D [mm]
105953	PRIMA 1.4ft VP ABS 3200/840	50	3260	3030	20,1	151	1,7	1175	700 - 960

The values stated for power consumption and luminous flux are in a tolerance of ± 7.5 %

FEATURES

IP69 | IP66 | up to -25°C | up to 50°C | 650°C | IK 06 | LED | WARRANTY 5 | D | 220-240 V 50/60 Hz | CRI >80 | CCT 4000 K 3 SDCM | L95 @25°C

CERTIFICATION

CE | CB test | HACCP | EPD

DOWNLOAD

INSTALLATION MANUAL | DATA SHEET | CE | CB | HACCP | EPD | LDT DATA

TREVOS

CODE | EAN

105953 | PRIMA 1.4ft VP ABS 3200/840 | 8596328059537



