TREVOS


CODE | EAN


**106000** | PRIMA 1.5ft VP ABSc 5500/840 ML | 8596328060007




- Degree of protection: IP66/IP69
- Ambient temperature: -25—45 °C
- Impact strength: IK06
- Life time: 150000 hours / L95 @25°C
- System efficacy: 156 lm/W
- Colour rendering index CRI: 80-89, 4000—4000 K
- Chromaticity tolerance (initial MacAdam): SDCM3
- Cable glands: M20x1.5 thread
- Protection class: I
- Max. number of luminaires per circuit breaker B16: 30
- Max. number of luminaires per circuit breaker C16: 51
- Flickering value Pst LM: 0,076
- Power factor: 0,95
- Stroboscope effect value SVM: 0,022
- Total harmonic distortion: 15
- Energy efficiency class of the light source: C

- Body: Dark grey ABS (high chemical resistance, UV stability, RAL 7001)
- Diffuser: Translucent acrylic (AC), UV stable, chemically resistant
- Reflector: Steel sheet, white (RAL 9003)
- Clips: Stainless steel + polyamide
- Sealing: Polyurethane (PUR), foam-filled base groove
- Connection: Screwless three-pole terminal block
- Resistant to dust, humidity and spraying water, the light fitting is suitable for both indoor and outdoor roofed industrial spaces
- Variable suspension spacing ranging from 970 - 1230 mm; enable the light to be installed onto suspension fittings left over from previous lighting
- Optimal mounting height: 3 to 8 m
- ON/OFF electronic driver (AC, DC on demand)




| Code | Type | Ta Max.: [°C] | Luminous flux of LED modules [lm] | Luminous flux of light fitting: [lm] | Power consumption: [W] | System efficacy: [lm/W] | Net weight: [kg] | A [mm] | D [mm] |
|---|---|---|---|---|---|---|---|---|---|
| 106000 | PRIMA 1.5ft VP ABSc 5500/840 ML | 45 | 5590 | 5200 | 33,3 | 156 | 2,0 | 1455 | 970 - 1230 |

The values stated for power consumption and luminous flux are in a tolerance of ± 7.5 %

FEATURES

IP69 | IP66 | up to $t_a$ -25°C | up to $t_a$ 45°C | 650°C | IK 06 | LED | WARRANTY 5 | D | 220-240 V 50/60 Hz | CRI >80 | CCT 4000 K 3 SDCM | L95 @25°C

CERTIFICATION

CE | CB test | HACCP | EPD

DOWNLOAD

INSTALLATION MANUAL | DATA SHEET | CE | CB | HACCP | EPD | LDT DATA

TREVOS

CODE | EAN

**106000** | PRIMA 1.5ft VP ABSc 5500/840 ML | 8596328060007





