TREVOS


CODE | EAN


**106796** | PRIMA 1.5ft TRS PCc 10000/840 DALI 3F | 8596328067969




- Degree of protection: IP66/IP69
- Ambient temperature: -25—35 °C
- Impact strength: IK10
- Life time: 150000 hours / L95 @25°C
- System efficacy: 155 lm/W
- Colour rendering index CRI: 80-89, 4000—4000 K
- Chromaticity tolerance (initial MacAdam): SDCM3
- Cable glands: M20x1.5 thread
- Protection class: I
- Max. number of luminaires per circuit breaker B16: 15
- Max. number of luminaires per circuit breaker C16: 25
- Flickering value Pst LM: 1
- Power factor: 0,95
- Stroboscope effect value SVM: 0,4
- Total harmonic distortion: 15
- Energy efficiency class of the light source: C

- Body: Clear PC (high mechanical resistance, UV stability)
- Diffuser: Clear PC (high mechanical resistance, UV stability)
- Reflector: Steel sheet, white (RAL 9003), modified for indirect lighting
- Clips: Stainless steel + polyamide
- Sealing: Polyurethane (PUR), foam-filled base groove
- Connection: Screwless seven-pole terminal block, 7-wire connecting cabling for feed-through installation (1.5 mm2 cross-section, 2.5 mm2 available on demand)
- Resistant to dust, humidity and spraying water, the light fitting is suitable for both indoor and outdoor roofed industrial spaces
- Variable suspension spacing ranging from 970 - 1230 mm; enable the light to be installed onto suspension fittings left over from previous lighting
- Optimal mounting height: 3 to 8 m
- Digitally dimmable DALI driver (AC/DC)




| Code | Type | Ta Max.: [°C] | Luminous flux of LED modules [lm] | Luminous flux of light fitting: [lm] | Power consumption: [W] | System efficacy: [lm/W] | Net weight: [kg] | A [mm] | D [mm] |
|---|---|---|---|---|---|---|---|---|---|
| 106796 | PRIMA 1.5ft TRS PCc 10000/840 DALI 3F | 35 | 10350 | 9730 | 62,9 | 155 | 2,3 | 1455 | 970 - 1230 |

The values stated for power consumption and luminous flux are in a tolerance of ± 7.5 %

FEATURES




CERTIFICATION




DOWNLOAD

INSTALLATION MANUAL | DATA SHEET | CE | CB | HACCP | EPD | LDT DATA

TREVOS

CODE | EAN

**106796** | PRIMA 1.5ft TRS PCc 10000/840 DALI 3F | 8596328067969





