TREVOS


CODE | EAN

106983 | BELTR LED 2.2ft SNS 3200/840 ML 3F | 8596328069833



- Degree of protection: IP44
- Ambient temperature: -25—40 °C
- Impact strength: IK08
- Life time: 150000 hours / L95 @25°C
- System efficacy: 131 lm/W
- Colour rendering index CRI: 80-89, 4000—4000 K
- Chromaticity tolerance (initial MacAdam): SDCM3
- Cable glands: rubber
- Protection class: I
- Max. number of luminaires per circuit breaker B16: 30
- Max. number of luminaires per circuit breaker C16: 51
- Flickering value Pst LM: 0,076
- Power factor: 0,95
- Stroboscope effect value SVM: 0,022
- Total harmonic distortion: 15
- Energy efficiency class of the light source: C

- Body: Steel sheet, white (RAL 9003)
- Diffuser: Translucent polycarbonate (PC), UV stable, impact resistant
- Reflector: Steel sheet, white (RAL 9003)
- Connection: Screwless three-pole terminal block
- Surface-mount, indoor light fitting for installation onto the ceiling or wall in public areas, option for series connection
- Opal diffuser made of highly permeable, translucent polycarbonate
- ON/OFF electronic driver (AC, DC on demand), microwave motion sensor



Code	Type	Luminous flux of LED modules [lm]	Luminous flux of light fitting: [lm]	Power consumption: [W]	System efficacy: [lm/W]	Net weight: [kg]	A [mm]	D [mm]
106983	BELTR LED 2.2ft SNS 3200/840 ML 3F	3250	2630	20,1	131	1,5	610	500

The values stated for power consumption and luminous flux are in a tolerance of ± 7.5 %

FEATURES

IP44 | up to ta -25°C | up to ta 40°C | 650°C | IK 08 | LED | WARRANTY 5 | D | 220-240 V 50/60 Hz | 3F | CRI >80 | CCT 4000 K 3 SDCM | L95 @25°C

CERTIFICATION

CE

DOWNLOAD

DATA SHEET | CE | LDT DATA

TREVOS

CODE | EAN

106983 | BELTR LED 2.2ft SNS 3200/840 ML 3F | 8596328069833

