



107074

NAON 1.4ft 4400/827-865 TW

8596328070747



- Degree of protection: IP20
- Ambient temperature: -25–35 °C
- Impact strength: IK02
- Life time: 50000 hours
- System efficacy: 127 lm/W
- Colour rendering index CRI: 80-89, 2700–6500 K
- Chromaticity tolerance (initial MacAdam): SDCM3
- Cable glands: rubber
- Protection class: I
- Max. number of luminaires per circuit breaker B16: 16
- Max. number of luminaires per circuit breaker C16: 27
- Flickering value Pst LM: 0,076
- Power factor: 0,95
- Stroboscope effect value SVM: 0,022
- Total harmonic distortion: 0,15
- Energy efficiency class of the light source: C

- Body: steel sheet, white (RAL 9003)
- Diffuser: acrylic (PMMA), sandblasted from both sides
- Reflector: steel sheet, white (RAL 9003)
- Connection: screwless five-pole terminal block
- Modern, low-profile light fitting for indoor lighting in offices, corridors and common rooms
- Opal diffuser made of highly permeable, translucent PMMA
- Digitally dimmable DALI driver DT8 (AC/DC), Tunable White modul 2700K - 6500K

Code	Type	Ta Max.: [°C]	Luminous flux of light fitting: [lm]	Power consumption: [W]	System efficacy: [lm/W]	Net weight: [kg]	A [mm]	D [mm]
107074	NAON 1.4ft 4400/827-865 TW	35	3310	26	127	3,6	1200	1130

The values stated for power consumption and luminous flux are in a tolerance of ± 7.5 %

FEATURES



CERTIFICATION



DOWNLOAD





CODE

EAN

**107074**

NAON 1.4ft 4400/827-865 TW

**8596328070747**

