TREVOS


CODE | EAN


107200 | PRIMA 1.5ft PIR PC 4000/840 COR | 8596328072000




- Degree of protection: IP65
- Ambient temperature: -25—50 °C
- Impact strength: IK10
- Life time: 150000 hours / L95 @25°C
- System efficacy: 154 lm/W
- Colour rendering index CRI: 80-89, 4000—4000 K
- Chromaticity tolerance (initial MacAdam): SDCM3
- Cable glands: M20x1.5 thread
- Protection class: I
- Max. number of luminaires per circuit breaker B16: 20
- Max. number of luminaires per circuit breaker C16: 34
- Flickering value Pst LM: 1
- Power factor: 0,95
- Stroboscope effect value SVM: 0,4
- Total harmonic distortion: 10
- Energy efficiency class of the light source: C

- Body: Grey PC (high mechanical resistance, UV stability, RAL 7035)
- Diffuser: Translucent PC (high mechanical resistance, UV stability)
- Reflector: Steel sheet, white (RAL 9003)
- Clips: Polyamide + 15 % fibreglass
- Sealing: Polyurethane (PUR), foam-filled base groove
- Connection: Screwless three-pole terminal block
- Resistant to dust, humidity and spraying water, the light fitting is suitable for both indoor and outdoor roofed industrial spaces
- Variable suspension spacing ranging from 970 - 1230 mm; enable the light to be installed onto suspension fittings left over from previous lighting
- Optimal mounting height: 3 to 8 m
- Digitally dimmable DALI driver with corridor function







Code	Type	Ta Max.: [°C]	Luminous flux of LED modules [lm]	Luminous flux of light fitting: [lm]	Power consumption: [W]	System efficacy: [lm/W]	Net weight: [kg]	A [mm]	D [mm]
107200	PRIMA 1.5ft PIR PC 4000/840 COR	50	4180	3890	25,3	154	2,2	1455	970 - 1230

The values stated for power consumption and luminous flux are in a tolerance of ± 7.5 %

FEATURES

IP65 | up to Ta -25°C | up to Ta 50°C | 850°C | IK10 | LED | WARRANTY 5 | D | 220-240 V 50/60 Hz | DALI | CRI >80 | CCT 4000 K 3 SDCM | L95 @25°C

CERTIFICATION

CE | HACCP

DOWNLOAD

INSTALLATION MANUAL | DATA SHEET | CE | HACCP | LDT DATA

TREVOS

CODE | EAN

107200 | PRIMA 1.5ft PIR PC 4000/840 COR | 8596328072000







