TREVOS


CODE | EAN

10740 | FUTURA 2.2ft ES ABS Al 3200/840 DALI | 8590515107407



- Degree of protection: IP66
- Ambient temperature: -25—50 °C
- Impact strength: IK06
- Life time: 200000 hours / L95 @25°C
- System efficacy: 169 lm/W
- Colour rendering index CRI: 80-89, 4000—4000 K
- Chromaticity tolerance (initial MacAdam): SDCM3
- Cable glands: M20x1.5 thread
- Protection class: I
- Max. number of luminaires per circuit breaker B16: 20
- Max. number of luminaires per circuit breaker C16: 85
- Flickering value Pst LM: 1
- Power factor: 0,95
- Stroboscope effect value SVM: 0,4
- Total harmonic distortion: 10
- Energy efficiency class of the light source: B

- Body: Dark grey ABS (high chemical resistance, UV stability, RAL 7001)
- Diffuser: Translucent acrylic (AC), UV stable, chemically resistant
- Reflector: Steel sheet, white (RAL 9003)
- Clips: Polyamide + 15 % fibreglass
- Sealing: Polyurethane (PUR), foam-filled base groove
- Connection: Screwless five-pole terminal block
- Unique design, resistant against humidity and dust, with IP66 enclosure rating and built-in aluminium heat sinks
- Optimal mounting height: 3.5 to 10 m
- Digitally dimmable DALI driver (AC/DC)



Code	Type	Ta Max.: [°C]	Luminous flux of LED modules [lm]	Luminous flux of light fitting: [lm]	Power consumption: [W]	System efficacy: [lm/W]	Net weight: [kg]	A [mm]	D [mm]
10740	FUTURA 2.2ft ES ABS Al 3200/840 DALI	50	3470	3050	18,1	169	1,6	612	475

The values stated for power consumption and luminous flux are in a tolerance of ± 7.5 %

FEATURES

IP66 | up to t_a -25°C | up to t_a 50°C | 650°C | IK 06 | LED | WARRANTY 5 | 220-240 V 50/60 Hz | DALI | CRI >80 | CCT 4000 K 3 SDCM | L95 @25°C

CERTIFICATION

CB test | HACCP | EPD

DOWNLOAD

INSTALLATION MANUAL | DATA SHEET | CE | ENEC | CB | HACCP | EPD | LDT DATA

TREVOS

CODE | EAN

10740 | FUTURA 2.2ft ES ABS Al 3200/840 DALI | 8590515107407

