TREVOS


CODE


107579 | NANOTTICA 1.5ft E-CON PCc 8000/840 ML M3hAt 2x5P | EAN 8596[illegible]75797




- Degree of protection: IP66/IP69
- Ambient temperature: 0—40 °C
- Impact strength: IK10
- Life time: 150000 hours / L95 @25°C
- System efficacy: 159 lm/W
- Colour rendering index CRI: 80-89, 4000—4000 K
- Chromaticity tolerance (initial MacAdam): SDCM3
- External terminal block, 3 or 5 poles, 1.5 or 2.5 mm2 wire cross-section
- Protection class: I
- Max. number of luminaires per circuit breaker B16: 25
- Max. number of luminaires per circuit breaker C16: 38
- Flickering value Pst LM: 0,076
- Power factor: 0,95
- Stroboscope effect value SVM: 0,022
- Total harmonic distortion: 10
- Energy efficiency class of the light source: C

- Body: Grey PC (high mechanical resistance, UV stability, RAL 7035)
- Diffuser: Clear PC with nano-optics (high mechanical resistance, UV stability)
- Reflector: Steel sheet, white (RAL 9003)
- Clips: Stainless steel + polyamide
- Sealing: Polyurethane (PUR), foam-filled base groove
- Connection: External 5-pole terminal block, conductor cross-section 1.5 mm² (2.5 mm² on request)
- Absolute control over emitted light thanks to patented nano-optics
- Variable suspension spacing ranging from 970 - 1230 mm; enable the light to be installed onto suspension fittings left over from previous lighting
- Basic beam angle: medium beam (MB); optimal mounting height: 3.5 to 8 m
- ON/OFF electronic driver (AC, DC on demand), emergency back-up power supply with automated self-testing and 3 hour runtime
- Emergency back-up power supply for permanent and emergency lighting, connected to L3 (lum. flux 440lm)







Code	Type	Ta Max.: [°C]	Luminous flux of LED modules [lm]	Luminous flux of light fitting: [lm]	Power consumption: [W]	System efficacy: [lm/W]	Net weight: [kg]	A [mm]	D [mm]
107579	NANOTTICA 1.5ft E-CON PCc 8000/840 ML M3hAt 2x5P	40	8020	7540	47,4	159	2,4	1455	970 - 1230

The values stated for power consumption and luminous flux are in a tolerance of ± 7.5 %

FEATURES

IP69 | IP66 | up to Ta 0°C | up to Ta 40°C | 850°C | IK 10 | LED | D | 220-240 V 50/60 Hz | EMERGENCY | CRI >80 | CCT 4000 K 3 SDCM | L95 @25°C

CERTIFICATION

CE | HACCP

DOWNLOAD

INSTALLATION MANUAL | DATA SHEET | CE | ENEC | HACCP | LDT DATA

TREVOS

CODE

107579 | NANOTTICA 1.5ft E-CON PCc 8000/840 ML M3hAt 2x5P | EAN 8596[illegible]75797







