TREVOS


CODE | EAN


107862 | FUTURA 2.4ft E-CON PCc Al 12800/840 2x3P | 8596328078620




- Degree of protection: IP66
- Ambient temperature: -25—35 °C
- Impact strength: IK10
- Life time: 150000 hours / L95 @25°C
- System efficacy: 162 lm/W
- Colour rendering index CRI: 80-89, 4000—4000 K
- Chromaticity tolerance (initial MacAdam): SDCM3
- Two external 3-pole terminal blocks, conductor cross-section 1.5 or 2.5 mm2
- Protection class: I
- Max. number of luminaires per circuit breaker B16: 26
- Max. number of luminaires per circuit breaker C16: 38
- Flickering value Pst LM: 0,043
- Power factor: 0,95
- Stroboscope effect value SVM: 0,004
- Total harmonic distortion: 10
- Energy efficiency class of the light source: C

- Body: Grey PC (high mechanical resistance, UV stability, RAL 7035)
- Diffuser: Translucent PC (high mechanical resistance, UV stability)
- Reflector: Steel sheet, white (RAL 9003)
- Clips: Stainless steel + polyamide
- Sealing: Polyurethane (PUR), foam-filled base groove
- Connection: External 3-pole terminal block, conductor cross-section 1.5 mm2 (2.5 mm2 on request)
- Unique design, resistant against humidity and dust, with IP66 enclosure rating and built-in aluminium heat sinks
- Optimal mounting height: 3.5 to 10 m
- ON/OFF electronic driver (AC, DC on demand)







Code	Type	Ta Max.: [°C]	Luminous flux of LED modules [lm]	Luminous flux of light fitting: [lm]	Power consumption: [W]	System efficacy: [lm/W]	Net weight: [kg]	A [mm]	D [mm]
107862	FUTURA 2.4ft E-CON PCc Al 12800/840 2x3P	35	12920	12140	74,8	162	2,8	1172	700

The values stated for power consumption and luminous flux are in a tolerance of ± 7.5 %

FEATURES

IP66 | up to Ta -25°C | up to Ta 35°C | 650°C | IK10 | LED | WARRANTY 5 | 220-240 V 50/60 Hz | CRI >80 | CCT 4000 K 3 SDCM | L95 @25°C

CERTIFICATION

CE | HACCP

DOWNLOAD

INSTALLATION MANUAL | DATA SHEET | CE | HACCP | LDT DATA

TREVOS

CODE | EAN

107862 | FUTURA 2.4ft E-CON PCc Al 12800/840 2x3P | 8596328078620



