TREVOS


CODE | EAN


107903 | TAURI 1.5ft 6800/840 MLC 3F | 8596328079030



- Degree of protection: IP20
- Ambient temperature: -25—50 °C
- Impact strength: IK08
- Life time: 100000 hours / L80 @25°C
- System efficacy: 144 lm/W
- Colour rendering index CRI: 80-89, 3000—6000 K
- Chromaticity tolerance (initial MacAdam): SDCM3
- Protection class: I
- Max. number of luminaires per circuit breaker B16: 32
- Max. number of luminaires per circuit breaker C16: 63
- Flickering value Pst LM: 1
- Power factor: 0,95
- Stroboscope effect value SVM: 0,4
- Total harmonic distortion: 20
- Energy efficiency class of the light source: C

- Reflector: Steel sheet, white (RAL 9003)
- Connection: Screwless five-pole terminal block, 5-wire connecting cabling for feed-through installation (1.5 mm2 cross-section, 2.5 mm2 available on demand)
- Indoor light fitting for corridors, school interiors, libraries, sanitary facilities, changing rooms, work areas and shop windows
- Opal diffuser made of highly permeable, translucent polycarbonate
- ON/OFF electronic driver (AC, DC on demand)





Code	Type	Ta Max.: [°C]	Luminous flux of LED modules [lm]	Luminous flux of light fitting: [lm]	Power consumption: [W]	System efficacy: [lm/W]	Net weight: [kg]	A [mm]	D [mm]
107903	TAURI 1.5ft 6800/840 MLC 3F	50	6840	6160	42,9	144	1,8	1470	1265

The values stated for power consumption and luminous flux are in a tolerance of ± 7.5 %

FEATURES



CERTIFICATION

DOWNLOAD

INSTALLATION MANUAL | DATA SHEET | CE | LDT DATA

TREVOS

CODE | EAN

107903 | TAURI 1.5ft 6800/840 MLC 3F | 8596328079030



