TREVOS


CODE | EAN


108680 | NANOTTICA 1.5ft ES PCc 8000/840 DALI M3hAt | 8596328086809




- Degree of protection: IP66/IP69
- Ambient temperature: 0—40 °C
- Impact strength: IK10
- Life time: 200000 hours / L95 @25°C
- System efficacy: 182 lm/W
- Colour rendering index CRI: 80-89, 4000—4000 K
- Chromaticity tolerance (initial MacAdam): SDCM3
- Cable glands: M20x1.5 thread
- Protection class: I
- Max. number of luminaires per circuit breaker B16: 20
- Max. number of luminaires per circuit breaker C16: 34
- Flickering value Pst LM: 1
- Power factor: 0,95
- Stroboscope effect value SVM: 0,4
- Total harmonic distortion: 10
- Energy efficiency class of the light source: B

- Body: Grey PC (high mechanical resistance, UV stability, RAL 7035)
- Diffuser: Clear PC with nano-optics (high mechanical resistance, UV stability)
- Reflector: Steel sheet, white (RAL 9003)
- Clips: Stainless steel + polyamide
- Sealing: Polyurethane (PUR), foam-filled base groove
- Connection: Screwless seven-pole terminal block
- Absolute control over emitted light thanks to patented nano-optics
- Variable suspension spacing ranging from 970 - 1230 mm; enable the light to be installed onto suspension fittings left over from previous lighting
- Basic beam angle: medium beam (MB); optimal mounting height: 3.5 to 8 m
- Digitally dimmable DALI driver (AC/DC), emergency back-up power supply with automated self-testing and 3 hour runtime
- Emergency back-up power supply for permanent and emergency lighting, connected to L3 (lum. flux 440lm)







Code	Type	Ta Max.: [°C]	Luminous flux of LED modules [lm]	Luminous flux of light fitting: [lm]	Power consumption: [W]	System efficacy: [lm/W]	Net weight: [kg]	A [mm]	D [mm]
108680	NANOTTICA 1.5ft ES PCc 8000/840 DALI M3hAt	40	8020	7540	41,4	182	2,3	1455	970 - 1230

The values stated for power consumption and luminous flux are in a tolerance of ± 7.5 %

FEATURES

IP66 | IP69 | up to 0°C | up to 40°C | 850°C | IK 10 | LED | 220-240 V 50/60 Hz | DALI | EMERGENCY | CRI >80 | CCT 4000 K 3 SDCM | L95 @25°C

CERTIFICATION

HACCP | EPD

DOWNLOAD

INSTALLATION MANUAL | DATA SHEET | CE | ENEC | HACCP | EPD | LDT DATA

TREVOS

CODE | EAN

108680 | NANOTTICA 1.5ft ES PCc 8000/840 DALI M3hAt | 8596328086809





