TREVOS

CODE | EAN

110034 | NAOS 2.4ft 6400/840 ML M3hAt | 8596328100345



- Degree of protection: IP40
- Ambient temperature: 0—35 °C
- Impact strength: IK02
- Life time: 150000 hours / L95 @25°C
- System efficacy: 141 lm/W
- Colour rendering index CRI: 80-89, 4000—4000 K
- Chromaticity tolerance (initial MacAdam): SDCM3
- Cable glands: rubber
- Protection class: I
- Max. number of luminaires per circuit breaker B16: 25
- Max. number of luminaires per circuit breaker C16: 38
- Flickering value Pst LM: 0,076
- Power factor: 0,95
- Stroboscope effect value SVM: 0,022
- Total harmonic distortion: 15
- Energy efficiency class of the light source: C

- Body: Steel sheet, white (RAL 9003)
- Diffuser: Acrylic (PMMA), sandblasted from both sides
- Connection: Screwless five-pole terminal block
- Modern, low-profile light fitting for indoor lighting in offices, corridors and common rooms
- Opal diffuser made of highly permeable, translucent PMMA
- ON/OFF electronic driver (AC, DC on demand), emergency back-up power supply with automated self-testing and 3 hour runtime
- Emergency back-up power supply for permanent and emergency lighting, connected to L3 (lum. flux 440lm)



Code	Type	Luminous flux of LED modules [lm]	Luminous flux of light fitting: [lm]	Power consumption: [W]	System efficacy: [lm/W]	Net weight: [kg]	A [mm]	D [mm]
110034	NAOS 2.4ft 6400/840 ML M3hAt	6520	5410	38,4	141	4,8	1180	1030

The values stated for power consumption and luminous flux are in a tolerance of ± 7.5 %

FEATURES

IP40 | up to ta 0°C | up to ta 35°C | 850°C | LED | D | 220-240 V 50/60 Hz | EMERGENCY | CRI >80 | CCT 4000 K 3 SDCM | L95 @25°C

CERTIFICATION

CE

DOWNLOAD

INSTALLATION MANUAL | DATA SHEET | CE | LDT DATA

TREVOS

CODE | EAN

110034 | NAOS 2.4ft 6400/840 ML M3hAt | 8596328100345






