TREVOS


CODE


110199 | NANOTTICA 1.4ft NB PCc 8000/840 DALI | EAN 8596328101991




- Degree of protection: IP66/IP69
- Ambient temperature: -25—35 °C
- Impact strength: IK10
- Life time: 150000 hours / L95 @25°C
- System efficacy: 152 lm/W
- Colour rendering index CRI: 80-89, 4000—4000 K
- Chromaticity tolerance (initial MacAdam): SDCM3
- Cable glands: M20x1.5 thread
- Protection class: I
- Max. number of luminaires per circuit breaker B16: 15
- Max. number of luminaires per circuit breaker C16: 25
- Flickering value Pst LM: 1
- Power factor: 0,95
- Stroboscope effect value SVM: 0,4
- Total harmonic distortion: 15
- Energy efficiency class of the light source: C

- Body: Grey PC (high mechanical resistance, UV stability, RAL 7035)
- Diffuser: Clear PC with nano-optics (high mechanical resistance, UV stability)
- Reflector: Steel sheet, white (RAL 9003)
- Clips: Stainless steel + polyamide
- Sealing: Polyurethane (PUR), foam-filled base groove
- Connection: Screwless five-pole terminal block
- Absolute control over emitted light thanks to patented nano-optics
- Variable suspension spacing ranging from 700 - 960 mm; enable the light to be installed onto suspension fittings left over from previous lighting
- Basic beam angle: narrow beam (NB); optimal mounting height: 7.5 to 12 m
- Digitally dimmable DALI driver (AC/DC)







Code	Type	Ta Max.: [°C]	Luminous flux of LED modules [lm]	Luminous flux of light fitting: [lm]	Power consumption: [W]	System efficacy: [lm/W]	Net weight: [kg]	A [mm]	D [mm]
110199	NANOTTICA 1.4ft NB PCc 8000/840 DALI	35	8160	7430	49,0	152	1,8	1175	700 - 960

The values stated for power consumption and luminous flux are in a tolerance of ± 7.5 %

FEATURES

IP66 | IP69 | up to -25°C | up to 35°C | 850°C | IK 10 | LED | WARRANTY 5 | D | 220-240 V 50/60 Hz | DALI | CRI >80 | CCT 4000 K 3 SDCM | L95 @25°C

CERTIFICATION

CE | CB test | HACCP

DOWNLOAD

INSTALLATION MANUAL | DATA SHEET | CE | ENEC | CB | HACCP | LDT DATA

TREVOS

CODE | EAN

110199 | NANOTTICA 1.4ft NB PCc 8000/840 DALI | 8596328101991





