TREVOS


CODE | EAN


112009 | PRIMA 1.2ft ES ABS 1600/840 | 8596328120091




- Degree of protection: IP66/IP69
- Ambient temperature: -25—50 °C
- Impact strength: IK06
- Life time: 200000 hours / L95 @25°C
- System efficacy: 172 lm/W
- Colour rendering index CRI: 80-89, 4000—4000 K
- Chromaticity tolerance (initial MacAdam): SDCM3
- Cable glands: M20x1.5 thread
- Protection class: I
- Max. number of luminaires per circuit breaker B16: 30
- Max. number of luminaires per circuit breaker C16: 51
- Energy efficiency class of the light source: B

- Body: Dark grey ABS (high chemical resistance, UV stability, RAL 7001)
- Diffuser: Translucent acrylic (AC), UV stable, chemically resistant
- Reflector: Steel sheet, white (RAL 9003)
- Clips: Polyamide + 15 % fibreglass
- Sealing: Polyurethane (PUR), foam-filled base groove
- Connection: Screwless three-pole terminal block
- Resistant to dust, humidity and spraying water, the light fitting is suitable for both indoor and outdoor roofed industrial spaces
- Variable suspension spacing ranging from 110 - 370 mm; enable the light to be installed onto suspension fittings left over from previous lighting
- Optimal mounting height: 3 to 8 m
- ON/OFF electronic driver (AC, DC on demand)







Code	Type	Ta Max.: [°C]	Luminous flux of LED modules [lm]	Luminous flux of light fitting: [lm]	Power consumption: [W]	System efficacy: [lm/W]	Net weight: [kg]	A [mm]	D [mm]
112009	PRIMA 1.2ft ES ABS 1600/840	50	1740	1620	9,4	172	0,9	615	110 - 370

The values stated for power consumption and luminous flux are in a tolerance of ± 7.5 %

FEATURES



CERTIFICATION



DOWNLOAD

INSTALLATION MANUAL | DATA SHEET | CE | HACCP | LDT DATA

TREVOS

CODE | EAN

112009 | PRIMA 1.2ft ES ABS 1600/840 | 8596328120091



