TREVOS

CODE

11258

FUTURA 2.2ft HE ABSc Al 6400/840 M3h


EAN


8590515112586




- Degree of protection: IP66
- Ambient temperature: 0—25 °C
- Impact strength: IK10
- Life time: 50000 hours
- System efficacy: 163 lm/W
- Colour rendering index CRI: 80-89, 4000—4000 K
- Chromaticity tolerance (initial MacAdam): SDCM3
- Cable glands: PG 13.5 thread
- Protection class: I
- Max. number of luminaires per circuit breaker B16: 16
- Max. number of luminaires per circuit breaker C16: 27
- Flickering value Pst LM: 0,076
- Power factor: 0,95
- Stroboscope effect value SVM: 0,022
- Total harmonic distortion: 15
- Energy efficiency class of the light source: B

- Body: dark grey ABS (high chemical resistance, UV stability, RAL 7001)
- Diffuser: translucent acrylic (AC), UV stable, chemically resistant
- Reflector: steel sheet, white (RAL 9003)
- Clips: stainless steel + polyamide
- Sealing: polyurethane (PUR), foam-filled base groove
- Connection: screwless five-pole terminal block
- Unique design, resistant against humidity and dust, with IP66 enclosure rating and built-in aluminium heat sinks
- High-efficiency light fitting with sulphur-resistant LED modules
- Optimal mounting height: 3.5 to 10 m
- ON/OFF electronic driver (AC, DC on demand), emergency back-up power supply with 3 hour runtime
- Emergency back-up power supply for permanent and emergency lighting, connected to L3 (lum. flux 440lm)







Code	Type	Ta Max.: [°C]	Luminous flux of LED modules [lm]	Luminous flux of light fitting: [lm]	Power consumption: [W]	System efficacy: [lm/W]	Net weight: [kg]	A [mm]	D [mm]
11258	FUTURA 2.2ft HE ABSc Al 6400/840 M3h	25	6650	5850	35,9	163	2,6	612	475

The values stated for power consumption and luminous flux are in a tolerance of ± 7.5 %

FEATURES

IP66 | up to 0°C | up to 25°C | 650°C | IK10 | LED | D | 220-240 V 50/60 Hz | EMERGENCY | CRI >80 | CCT 4000 K 3 SDCM | L90 B10

CERTIFICATION

CE | HACCP

DOWNLOAD

INSTALLATION MANUAL | DATA SHEET | CE | HACCP | LDT DATA



TREVOS


CODE | EAN


11258 | FUTURA 2.2ft HE ABSc Al 6400/840 M3h | 8590515112586









TREVOS www.trevos.eu

29.3.2024