TREVOS

CODE

11259

FUTURA 2.4ft SR ABSc AI 6400/840


EAN


8590515112593




- Degree of protection: IP66
- Ambient temperature: -25—50 °C
- Impact strength: IK10
- Life time: 150000 hours / L95 @25°C
- System efficacy: 169 lm/W
- Colour rendering index CRI: 80-89, 4000—4000 K
- Chromaticity tolerance (initial MacAdam): SDCM3
- Cable glands: M20x1.5 thread
- Protection class: I
- Max. number of luminaires per circuit breaker B16: 25
- Max. number of luminaires per circuit breaker C16: 38
- Flickering value Pst LM: 0,076
- Power factor: 0,95
- Stroboscope effect value SVM: 0,022
- Total harmonic distortion: 15
- Energy efficiency class of the light source: B

- Body: Dark grey ABS (high chemical resistance, UV stability, RAL 7001)
- Diffuser: Translucent ABS (high chemical resistance, UV stability)
- Reflector: Steel sheet, white (RAL 9003)
- Clips: Stainless steel + polyamide
- Sealing: Polyurethane (PUR), foam-filled base groove
- Connection: Screwless three-pole terminal block
- Unique design, resistant against humidity and dust, with IP66 enclosure rating and built-in aluminium heat sinks
- High-efficiency light fitting with sulphur-resistant LED modules
- Optimal mounting height: 3.5 to 10 m
- ON/OFF electronic driver (AC, DC on demand)







Code	Type	Ta Max.: [°C]	Luminous flux of LED modules [lm]	Luminous flux of light fitting: [lm]	Power consumption: [W]	System efficacy: [lm/W]	Net weight: [kg]	A [mm]	D [mm]
11259	FUTURA 2.4ft SR ABSc AI 6400/840	50	6780	6170	36,6	169	2,4	1172	700

The values stated for power consumption and luminous flux are in a tolerance of ± 7.5 %

FEATURES

IP66 · up to -25°C · up to 50°C · 650°C · IK10 · LED · WARRANTY 5 · D · 220-240 V 50/60 Hz · CRI >80 · CCT 4000 K 3 SDCM · L95 @25°C

CERTIFICATION

CE · HACCP

DOWNLOAD

INSTALLATION MANUAL · DATA SHEET · CE · HACCP · LDT DATA

TREVOS

CODE | EAN

11259 | FUTURA 2.4ft SR ABSc Al 6400/840 | 8590515112593

