TREVOS

CODE

11346

FUTURA 2.2ft SR ABSc Al 3200/840 DALI


EAN


8590515113460




- Degree of protection: IP66
- Ambient temperature: -25—50 °C
- Impact strength: IK10
- Life time: 150000 hours / L95 @25°C
- System efficacy: 164 lm/W
- Colour rendering index CRI: 80-89, 4000—4000 K
- Chromaticity tolerance (initial MacAdam): SDCM3
- Cable glands: M20x1.5 thread
- Protection class: I
- Max. number of luminaires per circuit breaker B16: 20
- Max. number of luminaires per circuit breaker C16: 85
- Flickering value Pst LM: 1
- Power factor: 0,95
- Stroboscope effect value SVM: 0,4
- Total harmonic distortion: 10
- Energy efficiency class of the light source: B

- Body: Dark grey ABS (high chemical resistance, UV stability, RAL 7001)
- Diffuser: Translucent ABS (high chemical resistance, UV stability)
- Reflector: Steel sheet, white (RAL 9003)
- Clips: Stainless steel + polyamide
- Sealing: Polyurethane (PUR), foam-filled base groove
- Connection: Screwless five-pole terminal block
- Unique design, resistant against humidity and dust, with IP66 enclosure rating and built-in aluminium heat sinks
- High-efficiency light fitting with sulphur-resistant LED modules
- Optimal mounting height: 3.5 to 10 m
- Digitally dimmable DALI driver (AC/DC)







Code	Type	Ta Max.: [°C]	Luminous flux of LED modules [lm]	Luminous flux of light fitting: [lm]	Power consumption: [W]	System efficacy: [lm/W]	Net weight: [kg]	A [mm]	D [mm]
11346	FUTURA 2.2ft SR ABSc Al 3200/840 DALI	50	3570	3250	19,8	164	1,6	612	475

The values stated for power consumption and luminous flux are in a tolerance of ± 7.5 %

FEATURES

IP66 · up to -25°C · up to 50°C · 650°C · IK10 · LED · WARRANTY 5 · D · 220-240 V 50/60 Hz · DALI · CRI >80 · CCT 4000 K 3 SDCM · L95 @25°C

CERTIFICATION

CE · HACCP

DOWNLOAD

INSTALLATION MANUAL · DATA SHEET · CE · HACCP · LDT DATA

TREVOS

CODE | EAN

11346 | FUTURA 2.2ft SR ABSc Al 3200/840 DALI | 8590515113460

