TREVOS

CODE

11497

PRIMA LED TUBE SLIM 2x150 PCc 3F


EAN

8590515114979




- Degree of protection: IP66
- Ambient temperature: -25—35 °C
- Impact strength: IK10
- System efficacy: 101 lm/W
- Chromaticity tolerance (initial MacAdam): SDCM3
- Cable glands: rubber (SBS)
- Protection class: I

- Body: Grey PC (high mechanical resistance, UV stability, RAL 7035)
- Diffuser: Clear PC (high mechanical resistance, UV stability)
- Reflector: Steel sheet, white (RAL 9003)
- Clips: Stainless steel + polyamide
- Sealing: Polyurethane (PUR), foam-filled base groove
- Connection: Screwless five-pole terminal block, 5-wire connecting cabling for feed-through installation (1.5 mm2 cross-section, 2.5 mm2 available on demand)
- Luminaire for indoor and covered outdoor industrial spaces intended for retrofitting an existing lighting system (LED TUBE)
- Total luminous flux and electric energy consumption are calculated using Osram SubstiTUBE T8 EM Value sources
- Optimal mounting height: 3 to 8 m







Code	Type	Ta Max.: [°C]	Luminous flux of LED modules [lm]	Luminous flux of light fitting: [lm]	Power consumption: [W]	System efficacy: [lm/W]	Net weight: [kg]	A [mm]	D [mm]
11497	PRIMA LED TUBE SLIM 2x150 PCc 3F	35	4000	3840	38,2	101	2,6	1572	940

The values stated for power consumption and luminous flux are in a tolerance of ± 7.5 %

FEATURES

IP66 · up to -25°C · up to 35°C · 850°C · IK10 · LED · WARRANTY 5 · D · 3F

CERTIFICATION

CE

DOWNLOAD

INSTALLATION MANUAL · DATA SHEET · CE

TREVOS

CODE

EAN

11497 | PRIMA LED TUBE SLIM 2x150 PCc 3F | 8590515114979



