TREVOS

CODE

14813

PRIMA LED Ex 1.4ft PCc 3200/840 3F


EAN


8590515148134




- Degree of protection: IP66
- Ambient temperature: -25—60 °C
- Impact strength: IK10
- Life time: 150000 hours / L95 @25°C
- System efficacy: 141 lm/W
- Cable glands: M20X1,5, ATEX thread
- Protection class: I
- Max. number of luminaires per circuit breaker B16: 30
- Max. number of luminaires per circuit breaker C16: 51
- Power factor: 0,95
- Energy efficiency class of the light source: C

- Body: Grey PC (high mechanical resistance, UV stability, RAL 7035)
- Diffuser: Translucent PC (high mechanical resistance, UV stability)
- Reflector: Steel sheet, white (RAL 9003)
- Clips: Stainless steel + polyamide
- Sealing: Polyurethane (PUR), foam-filled base groove
- Connection: Screwless five-pole terminal block, 5-wire connecting cabling for feed-through installation (1.5 mm2 cross-section, 2.5 mm2 available on demand)
- Light fitting certified for environments with potentially explosive atmospheres created by gas, dust or flammable vapours, group II, category 3 (zone 2/22)
- For use in potentially explosive environments. For definition, see the assembly manual and certificate
- Optimal mounting height: 3 to 8 m
- ON/OFF electronic driver (AC, DC on demand)







Code	Type	Ta Max.: [°C]	Luminous flux of LED modules [lm]	Luminous flux of light fitting: [lm]	Power consumption: [W]	System efficacy: [lm/W]	Net weight: [kg]	A [mm]	D [mm]
14813	PRIMA LED Ex 1.4ft PCc 3200/840 3F	60	3260	2840	20,1	141	3,4	1272	700

The values stated for power consumption and luminous flux are in a tolerance of ± 7.5 %

FEATURES

IP66 · up to t_a -25°C · up to t_a 60°C · IK10 · LED · WARRANTY 5 · D · 220-240 V 50/60 Hz · 3F · CCT 4000 K 3 SDCM · L95 @25°C

CERTIFICATION

CE · CB test · EAC · Ex · ATEX

DOWNLOAD

INSTALLATION MANUAL · DATA SHEET · CE · CB · EAC · ATEX · UKEX · CNBOP · LDT DATA

TREVOS

CODE | EAN

14813 | PRIMA LED Ex 1.4ft PCc 3200/840 3F | 8590515148134







