




- Degree of protection: IP66
- Ambient temperature: -25–60 °C
- Impact strength: IK10
- Life time: 50000 hours
- System efficacy: 156 lm/W
- Cable glands: M20X1,5, ATEX thread
- Protection class: I
- Max. number of luminaires per circuit breaker B16: 30
- Max. number of luminaires per circuit breaker C16: 51
- Power factor: 0,95
- Energy efficiency class of the light source: D

- Body: grey PC (high mechanical resistance, UV stability, RAL 7035)
- Diffuser: translucent PC (high mechanical resistance, UV stability)
- Reflector: steel sheet, white (RAL 9003)
- Clips: stainless steel + polyamide
- Sealing: polyurethane (PUR), foam-filled base groove
- Connection: screwless five-pole terminal block, 5-wire connecting cabling for feed-through installation (1.5 mm2 cross-section, 2.5 mm2 available on demand)
- Light fitting certified for environments with potentially explosive atmospheres created by gas, dust or flammable vapours, group II, category 3 (zone 2/22)
- For use in potentially explosive environments. For definition, see the assembly manual and certificate
- Optimal mounting height: 3 to 8 m
- ON/OFF electronic driver (AC, DC on demand)



FEATURES

IP66

up to

-25°C

up to

60°C

IK 10

LED

WARRANTY 5

220-240 V
50/60 Hz

3F

CCT

4000 K

3 SDCM

L90

B10

CERTIFICATION



DOWNLOAD

INSTALLATION MANUAL

DATA SHEET

CE

CB

EAC

ATEX

UKEX

LDT DATA



14853

PRIMA LED Ex 2.4ft PCc 6400/840 3F

8590515148530

