TREVOS

CODE

14935

PRIMA LED Ex 1.5ft PCc 4000/840 DALI M3h


EAN


8590515149353




- Degree of protection: IP66
- Ambient temperature: 0—50 °C
- Impact strength: IK10
- Life time: 50000 hours
- System efficacy: 154 lm/W
- Cable glands: M20X1,5, ATEX thread
- Protection class: I
- Max. number of luminaires per circuit breaker B16: 21
- Max. number of luminaires per circuit breaker C16: 35
- Power factor: 0,95
- Energy efficiency class of the light source: D

- Body: grey PC (high mechanical resistance, UV stability, RAL 7035)
- Diffuser: translucent PC (high mechanical resistance, UV stability)
- Reflector: steel sheet, white (RAL 9003)
- Clips: stainless steel + polyamide
- Sealing: polyurethane (PUR), foam-filled base groove
- Connection: screwless seven-pole terminal block
- Light fitting certified for environments with potentially explosive atmospheres created by gas, dust or flammable vapours, group II, category 3 (zone 2/22)
- For use in potentially explosive environments. For definition, see the assembly manual and certificate
- Optimal mounting height: 3 to 8 m
- Digitally dimmable DALI driver (AC/DC), emergency back-up power supply with 3 hour runtime
- Emergency back-up power supply for permanent and emergency lighting, connected to L3 (lum. flux 440lm)







Code	Type	Ta Max.: [°C]	Luminous flux of LED modules [lm]	Luminous flux of light fitting: [lm]	Power consumption: [W]	Net weight: [kg]	A [mm]	D [mm]
14935	PRIMA LED Ex 1.5ft PCc 4000/840 DALI M3h	50	4520	4150	27	4,2	1572	940

The values stated for power consumption and luminous flux are in a tolerance of ± 7.5 %

FEATURES



CERTIFICATION

DOWNLOAD

INSTALLATION MANUAL | DATA SHEET | CE | CB | EAC | ATEX | UKEX | LDT DATA

TREVOS

CODE | EAN

14935 | PRIMA LED Ex 1.5ft PCc 4000/840 DALI M3h | 8590515149353







