TREVOS


CODE | EAN


20477 | FUTURA 2.2ft VP PCc Al 4400/840 DALI M3hAt | 8590515204779




- Degree of protection: IP66
- Ambient temperature: 0—40 °C
- Impact strength: IK10
- Life time: 150000 hours / L95 @25°C
- System efficacy: 155 lm/W
- Colour rendering index CRI: 80-89, 4000—4000 K
- Chromaticity tolerance (initial MacAdam): SDCM3
- Cable glands: M20x1.5 thread
- Protection class: I
- Max. number of luminaires per circuit breaker B16: 20
- Max. number of luminaires per circuit breaker C16: 34
- Flickering value Pst LM: 1
- Power factor: 0,95
- Stroboscope effect value SVM: 0,4
- Total harmonic distortion: 10
- Energy efficiency class of the light source: C

- Body: Grey PC (high mechanical resistance, UV stability, RAL 7035)
- Diffuser: Translucent PC (high mechanical resistance, UV stability)
- Reflector: Steel sheet, white (RAL 9003)
- Clips: Stainless steel + polyamide
- Sealing: Polyurethane (PUR), foam-filled base groove
- Connection: Screwless seven-pole terminal block
- Unique design, resistant against humidity and dust, with IP66 enclosure rating and built-in aluminium heat sinks
- Type BVPB-01 polyamide vent plug, size M12x1.5
- Optimal mounting height: 3.5 to 10 m
- Digitally dimmable DALI driver (AC/DC), emergency back-up power supply with automated self-testing and 3 hour runtime
- Emergency back-up power supply for permanent and emergency lighting, connected to L3 (lum. flux 440lm)







Code	Type	Ta Max.: [°C]	Luminous flux of LED modules [lm]	Luminous flux of light fitting: [lm]	Power consumption: [W]	System efficacy: [lm/W]	Net weight: [kg]	A [mm]	D [mm]
20477	FUTURA 2.2ft VP PCc Al 4400/840 DALI M3hAt	40	4680	4400	28,3	155	1,8	612	475

The values stated for power consumption and luminous flux are in a tolerance of ± 7.5 %

FEATURES

IP66 | up to 0°C | up to 40°C | 650°C | IK10 | LED | D | 220-240 V 50/60 Hz | DALI | EMERGENCY | CRI >80 | CCT 4000 K 3 SDCM | L95 @25°C

CERTIFICATION

CE | HACCP

DOWNLOAD

INSTALLATION MANUAL | DATA SHEET | CE | HACCP | LDT DATA

TREVOS

CODE | EAN

20477 | FUTURA 2.2ft VP PCc Al 4400/840 DALI M3hAt | 8590515204779

