TREVOS


CODE | EAN

22435 | SB LED 1.4ft 4400/840 | 8590515224357



- Degree of protection: IP20
- Ambient temperature: 0—35 °C
- Impact strength: IK08
- Life time: 50000 hours
- System efficacy: 143 lm/W
- Colour rendering index CRI: 80-89, 4000—4000 K
- Chromaticity tolerance (initial MacAdam): SDCM3
- Protection class: I
- Max. number of luminaires per circuit breaker B16: 65
- Max. number of luminaires per circuit breaker C16: 65
- Flickering value Pst LM: 1
- Power factor: 0,95
- Stroboscope effect value SVM: 0,4
- Total harmonic distortion: 20
- Energy efficiency class of the light source: D

- Body: aluminium profile, white (RAL 9003)
- Diffuser: translucent polycarbonate (PC), UV stable, impact resistant
- Connection: screwless three-pole terminal block
- Indoor light fitting for sanitary facilities, kitchen units, changing rooms, work areas and shop windows
- With an integrated switch in the plastic cap on the side
- Sliding spacers for mounting the light fitting
- ON/OFF electronic driver (AC, DC on demand)



Code	Type	Ta Max.: [°C]	Luminous flux of LED modules [lm]	Luminous flux of light fitting: [lm]	Power consumption: [W]	System efficacy: [lm/W]	Net weight: [kg]	A [mm]	D [mm]
22435	SB LED 1.4ft 4400/840	35	4670	4250	29,8	143	1	1150	1020

The values stated for power consumption and luminous flux are in a tolerance of ± 7.5 %

FEATURES

IP20 | up to Ta 0°C | up to Ta 35°C | 650°C | IK 08 | LED | WARRANTY 5 | D | 220-240 V 50/60 Hz | CRI >80 | CCT 4000 K 3 SDCM | L90 B10

CERTIFICATION

CE

DOWNLOAD

INSTALLATION MANUAL | DATA SHEET | CE | LDT DATA

TREVOS

CODE | EAN

22435 | SB LED 1.4ft 4400/840 | 8590515224357







