TREVOS


CODE

31526 | INNOVA 1.4ft PC 8800/840 1x5P | EAN 8590515315260




- Degree of protection: IP66/IP69
- Ambient temperature: -25—40 °C
- Impact strength: IK10
- Life time: 150000 hours / L95 @25°C
- System efficacy: 160 lm/W
- Colour rendering index CRI: 80-89, 4000—4000 K
- Chromaticity tolerance (initial MacAdam): SDCM3
- One external 5-pole terminal block, conductor cross-section 1.5 or 2.5 mm2
- Protection class: I
- Max. number of luminaires per circuit breaker B16: 25
- Max. number of luminaires per circuit breaker C16: 38
- Flickering value Pst LM: 0,043
- Power factor: 0,95
- Stroboscope effect value SVM: 0,004
- Total harmonic distortion: 10
- Energy efficiency class of the light source: C

- Body: Grey PC (high mechanical resistance, UV stability, RAL 7035)
- Diffuser: Translucent PC (high mechanical resistance, UV stability)
- Reflector: Steel sheet, white (RAL 9003)
- Connection: External 5-pole terminal block, conductor cross-section 1.5 mm² (2.5 mm² on request)
- Fully automated and comprehensive inspection of functionality and tightness during production, venting membrane prevents the creation of negative pressure or condensation
- Variable suspension spacing ranging from 420 - 700 mm; enable the light to be installed onto suspension fittings left over from previous lighting
- Basic beam angle, optimal mounting height of up to 6 m
- ON/OFF electronic driver (AC, DC on demand)
- External terminal box for connecting a power lead - plug&play system







Code	Type	Ta Max.: [°C]	Luminous flux of LED modules [lm]	Luminous flux of light fitting: [lm]	Power consumption: [W]	System efficacy: [lm/W]	Net weight: [kg]	A [mm]	D [mm]
31526	INNOVA 1.4ft PC 8800/840 1x5P	40	8980	8440	52,8	160	1,6	1175	420 - 700

The values stated for power consumption and luminous flux are in a tolerance of ± 7.5 %

FEATURES

IP69 IP66 up to -25°C up to 40°C 850°C IK10 LED WARRANTY 5 D 220-240 V 50/60 Hz CRI >80 CCT 4000 K 3 SDCM L95 @25°C

CERTIFICATION

CE CB test ESČ HACCP

DOWNLOAD

INSTALLATION MANUAL | DATA SHEET | CE | CB | ESČ | HACCP | LDT DATA

TREVOS

CODE | EAN

31526 | INNOVA 1.4ft PC 8800/840 1x5P | 8590515315260













