TREVOS

CODE

31537

INNOVA 1.5ft PC 8000/840 DALI 1x5P


EAN

8590515315376




- Degree of protection: IP66/IP69
- Ambient temperature: -25—45 °C
- Impact strength: IK10
- Life time: 150000 hours / L95 @25°C
- System efficacy: 159 lm/W
- Colour rendering index CRI: 80-89, 4000—4000 K
- Chromaticity tolerance (initial MacAdam): SDCM3
- One external 5-pole terminal block, conductor cross-section 1.5 or 2.5 mm2
- Protection class: I
- Max. number of luminaires per circuit breaker B16: 20
- Max. number of luminaires per circuit breaker C16: 34
- Flickering value Pst LM: 1
- Power factor: 0,95
- Stroboscope effect value SVM: 0,4
- Total harmonic distortion: 10
- Energy efficiency class of the light source: C

- Body: Grey PC (high mechanical resistance, UV stability, RAL 7035)
- Diffuser: Translucent PC (high mechanical resistance, UV stability)
- Reflector: Steel sheet, white (RAL 9003)
- Connection: External 5-pole terminal block, conductor cross-section 1.5 mm² (2.5 mm² on request)
- Fully automated and comprehensive inspection of functionality and tightness during production, venting membrane prevents the creation of negative pressure or condensation
- Variable suspension spacing ranging from 700 - 980 mm; enable the light to be installed onto suspension fittings left over from previous lighting
- Basic beam angle, optimal mounting height of up to 6 m
- Digitally dimmable DALI driver (AC/DC)
- External terminal box for connecting a power lead - plug&play system







Code	Type	Ta Max.: [°C]	Luminous flux of LED modules [lm]	Luminous flux of light fitting: [lm]	Power consumption: [W]	System efficacy: [lm/W]	Net weight: [kg]	A [mm]	D [mm]
31537	INNOVA 1.5ft PC 8000/840 DALI 1x5P	45	8020	7540	47,4	159	1,9	1455	700 - 980

The values stated for power consumption and luminous flux are in a tolerance of ± 7.5 %

FEATURES

IP66 · IP69 · up to t_a -25°C · up to t_a 45°C · 850°C · IK 10 · LED · WARRANTY 5 · D · 220-240 V 50/60 Hz · DALI · CRI >80 · CCT 4000 K 3 SDCM · L95 @25°C

CERTIFICATION

CE · CB test · ESČ · HACCP

DOWNLOAD

INSTALLATION MANUAL · DATA SHEET · CE · CB · ESČ · HACCP · LDT DATA

TREVOS

CODE | EAN

31537 | INNOVA 1.5ft PC 8000/840 DALI 1x5P | 8590515315376













