



37110


BELTR LED TUBE 1x60

8590515371105



- Degree of protection: IP40
- Ambient temperature: -25–35 °C
- Impact strength: IK08
- Life time: 50000 hours
- System efficacy: 86 lm/W
- Chromaticity tolerance (initial MacAdam): SDCM3
- Cable glands: rubber
- Protection class: I

- Body: steel sheet, white (RAL 9003)
- Diffuser: translucent polycarbonate (PC), UV stable, impact resistant
- Reflector: steel sheet, white (RAL 9003)
- Connection: screwless three-pole terminal block
- Surface-mount, indoor light fitting for installation onto the ceiling or wall in public areas, option for series connection
- Total luminous flux and electric energy consumption are calculated using Osram SubstiTUBE T8 EM Value sources



Code	Type	Luminous flux of LED modules [lm]	Net weight: [kg]	A [mm]	D [mm]
37110	BELTR LED TUBE 1x60	800	0,5	635	450

The values stated for power consumption and luminous flux are in a tolerance of $\pm 7.5\%$

FEATURES



CERTIFICATION



DOWNLOAD

- [INSTALLATION MANUAL](#)
- [DATA SHEET](#)
- [CE](#)



37110

BELTR LED TUBE 1x60

8590515371105

