TREVOS

CODE

41539 | PLEXI LED 101 NM3h | EAN 8590515415397

- Degree of protection: IP20
- Ambient temperature: 0—40 °C
- Impact strength: IK08
- Life time: 50000 hours
- Protection class: I
- Power factor: 0,95
- Energy efficiency class of the light source: D

- Body: steel sheet, aluminium white colour (RAL 9006)
- Diffuser: clear acrylic glass, UV stable
- Connection: screwless five-pole terminal block
- Luminaire for emergency and orientation lighting of corridors, offices, warehouses, production halls
- Can be connected for both permanent (SA) and emergency (SE) lighting
- Emergency back-up power supply for temporary emergency lighting, connected to L3 (lum. flux 440lm)



Code	Type	Net weight: [kg]
41539	PLEXI LED 101 NM3h	2,3

The values stated for power consumption and luminous flux are in a tolerance of ± 7.5 %

FEATURES

IP20 | up to ta 0°C | up to ta 40°C | IK 08 | LED | D | 220-240 V 50/60 Hz | L80 B20

CERTIFICATION

CE

DOWNLOAD

INSTALLATION MANUAL | DATA SHEET | CE

TREVOS

CODE | EAN

41539 | PLEXI LED 101 NM3h | 8590515415397