TREVOS


CODE | EAN


50414 | ALUMAX LED 1.2ft 1300/840 M1h | 8590515504145




- Degree of protection: IP66
- Ambient temperature: 0—25 °C
- Impact strength: IK10
- Life time: 50000 hours
- System efficacy: 122 lm/W
- Colour rendering index CRI: 80-89, 4000—4000 K
- Chromaticity tolerance (initial MacAdam): SDCM3
- Cable glands: brass, M18X1.5
- Protection class: I
- Max. number of luminaires per circuit breaker B16: 50
- Max. number of luminaires per circuit breaker C16: 85
- Flickering value Pst LM: 0,091
- Power factor: 0,95
- Stroboscope effect value SVM: 0,013
- Total harmonic distortion: 15
- Energy efficiency class of the light source: D

- Body: grey aluminium profile, powder coated
- Diffuser: satin, heat-strengthened safety glass
- Reflector: steel sheet, white (RAL 9003)
- Clips: stainless steel
- Sealing: polyurethane (PUR) in the groove on the body
- Connection: screwless five-pole terminal block
- Chemically resistant, dustproof and waterproof industrial light fitting made of painted aluminium alloy
- Heat-strengthened safety glass with shatter pursuant to ČSN EN 12150-1
- ON/OFF electronic driver (AC, DC on demand), emergency back-up power supply with 1 hour runtime
- Emergency back-up power supply for permanent and emergency lighting, connected to L3 (lum. flux 440lm)







Code	Type	Ta Max.: [°C]	Luminous flux of LED modules [lm]	Luminous flux of light fitting: [lm]	Power consumption: [W]	System efficacy: [lm/W]	Net weight: [kg]	A [mm]	D [mm]
50414	ALUMAX LED 1.2ft 1300/840 M1h	25	1310	1000	8,2	122	2,2	624	534

The values stated for power consumption and luminous flux are in a tolerance of ± 7.5 %

FEATURES

IP66 | up to ta 0°C | up to ta 25°C | 960°C | IK10 | LED | D | 220-240 V 50/60 Hz | EMERGENCY | CRI >80 | CCT 4000 K 3 SDCM | L90 B10

CERTIFICATION

CE

DOWNLOAD

INSTALLATION MANUAL | DATA SHEET | CE | LDT DATA

TREVOS

CODE | EAN

50414 | ALUMAX LED 1.2ft 1300/840 M1h | 8590515504145