TREVOS

CODE

51560

MIDDLE EAST Ta 55 1.5ft PCc 5500/840


EAN


8590515515608




- Degree of protection: IP66
- Ambient temperature: -25—55 °C
- Impact strength: IK10
- Life time: 150000 hours / L95 @25°C
- System efficacy: 141 lm/W
- Colour rendering index CRI: 80-89, 4000—4000 K
- Chromaticity tolerance (initial MacAdam): SDCM3
- Cable glands: M20x1.5 thread
- Protection class: I
- Max. number of luminaires per circuit breaker B16: 30
- Max. number of luminaires per circuit breaker C16: 51
- Flickering value Pst LM: 0,043
- Power factor: 0,95
- Stroboscope effect value SVM: 0,004
- Total harmonic distortion: 10
- Energy efficiency class of the light source: C

- Body: Grey PC (high mechanical resistance, UV stability, RAL 7035)
- Diffuser: Translucent PC (high mechanical resistance, UV stability)
- Reflector: Steel sheet, white (RAL 9003)
- Clips: Stainless steel + polyamide
- Sealing: Polyurethane (PUR), foam-filled base groove
- Connection: Screwless three-pole terminal block
- Version optimized for spaces with an ambient temperature of up to 55°C
- Optimal mounting height: 3.5 to 10 m
- ON/OFF electronic driver (AC, DC on demand)







Code	Type	Ta Max.: [°C]	Luminous flux of LED modules [lm]	Luminous flux of light fitting: [lm]	Power consumption: [W]	System efficacy: [lm/W]	Net weight: [kg]	A [mm]	D [mm]
51560	MIDDLE EAST Ta 55 1.5ft PCc 5500/840	55	5080	4780	33,9	141	2,3	1452	940

The values stated for power consumption and luminous flux are in a tolerance of ± 7.5 %

FEATURES

IP66 | up to -25°C | up to 55°C | 650°C | IK10 | LED | WARRANTY 5 | 220-240 V 50/60 Hz | CRI >80 | CCT 4000 K 3 SDCM | L95 @25°C

CERTIFICATION

CE | CB test | ESČ | EMC

DOWNLOAD

INSTALLATION MANUAL | DATA SHEET | CE | CB | ESČ | EMC | LDT DATA

TREVOS

CODE | EAN

51560 | MIDDLE EAST Ta 55 1.5ft PCc 5500/840 | 8590515515608









