TREVOS

CODE


54530 | BELTR LED 2.1ft NM1hAt | 8590515545308

EAN



- Degree of protection: IP44
- Ambient temperature: 0—40 °C
- Impact strength: IK08
- Life time: 50000 hours
- Cable glands: rubber
- Protection class: I
- Max. number of luminaires per circuit breaker B16: 100
- Max. number of luminaires per circuit breaker C16: 170
- Power factor: 0,95
- Energy efficiency class of the light source: D

- Body: steel sheet, white (RAL 9003)
- Diffuser: translucent polycarbonate (PC), UV stable, impact resistant
- Reflector: steel sheet, white (RAL 9003)
- Connection: screwless five-pole terminal block
- Surface-mount, indoor light fitting for installation onto the ceiling or wall in public areas, option for series connection
- Opal diffuser made of highly permeable, translucent polycarbonate
- Emergency back-up power supply with autotest and 1 hour runtime
- Emergency back-up power supply for temporary emergency lighting, connected to L3 (lum. flux 440lm)



Code	Type	Luminous flux of LED modules [lm]	Net weight: [kg]
54530	BELTR LED 2.1ft NM1hAt	500	1,2

The values stated for power consumption and luminous flux are in a tolerance of ± 7.5 %

FEATURES

IP44 | up to ta 0°C | up to ta 40°C | IK 08 | LED | D | 220-240 V 50/60 Hz | L80 B20

CERTIFICATION

CE

DOWNLOAD

INSTALLATION MANUAL | DATA SHEET | CE | LDT DATA

TREVOS

CODE | EAN

54530 | BELTR LED 2.1ft NM1hAt | 8590515545308

