TREVOS


CODE | EAN


62443 | FUTURA 2.2ft PCc NM3hAt | 8590515624430




- Degree of protection: IP66
- Ambient temperature: 5—50 °C
- Impact strength: IK10
- Life time: 150000 hours / L95 @25°C
- System efficacy: 133 lm/W
- Cable glands: M20x1.5 thread
- Protection class: I
- Max. number of luminaires per circuit breaker B16: 100
- Max. number of luminaires per circuit breaker C16: 170
- Energy efficiency class of the light source: C

- Body: Grey PC (high mechanical resistance, UV stability, RAL 7035)
- Diffuser: Translucent PC (high mechanical resistance, UV stability)
- Reflector: Steel sheet, white (RAL 9003)
- Clips: Stainless steel + polyamide
- Sealing: Polyurethane (PUR), foam-filled base groove
- Connection: Screwless five-pole terminal block
- Resistant to humidity and dust, with IP66 enclosure rating
- Optimal mounting height: 3.5 to 10 m
- Emergency back-up power supply with autotest and 3 hour runtime
- Emergency back-up power supply for temporary emergency lighting, connected to L3 (lum. flux 440lm)







Code	Type	Luminous flux of light fitting: [lm]	Power consumption: [W]	Net weight: [kg]
62443	FUTURA 2.2ft PCc NM3hAt	440	3,3	1,4

The values stated for power consumption and luminous flux are in a tolerance of ± 7.5 %

FEATURES

IP66 | up to ta 50°C | IK 10 | LED | 220-240 V 50/60 Hz | CCT 4000 K 3 SDCM | L95 @25°C

CERTIFICATION

CE | HACCP

DOWNLOAD

INSTALLATION MANUAL | DATA SHEET | CE | HACCP

TREVOS

CODE | EAN

62443 | FUTURA 2.2ft PCc NM3hAt | 8590515624430









