



63879

MO SLIM 1.5ft 3250/840

8590515638796



- Degree of protection: IP20
- Impact strength: IK08
- Life time: 50000 hours
- System efficacy: 143 lm/W
- Colour rendering index CRI: 80-89, 4000–4000 K
- Chromaticity tolerance (initial MacAdam): SDCM3
- Protection class: I
- Flickering value Pst LM: 0,008
- Power factor: 0,95
- Stroboscope effect value SVM: 0,012
- Energy efficiency class of the light source: D

- Body: aluminium profile, white (RAL 9003)
- Diffuser: translucent polycarbonate (PC), UV stable, impact resistant
- Reflector: steel sheet, white (RAL 9003)
- Connection: 2x screwless, five-pole terminal block, three-phase interconnection
- Suspended indoor light fitting with accessories for various installation configurations either separately or in groups
- The light fitting does not include end caps, couplers or suspender. Must be ordered separately
- Opal diffuser made of highly permeable, translucent polycarbonate
- ON/OFF electronic driver (AC, DC on demand)



| Code | Type | Luminous flux of LED modules [lm] | Luminous flux of light fitting: [lm] | Power consumption: [W] | System efficacy: [lm/W] | Net weight: [kg] | A [mm] | D [mm] |
|-------|------------------------|-----------------------------------|--------------------------------------|------------------------|-------------------------|------------------|--------|--------|
| 63879 | MO SLIM 1.5ft 3250/840 | 3240 | 2790 | 19,5 | 143 | 3,4 | 1410 | 1410 |

The values stated for power consumption and luminous flux are in a tolerance of ± 7.5 %

FEATURES



CERTIFICATION



DOWNLOAD





63879

MO SLIM 1.5ft 3250/840

8590515638796

