



63912

MO SLIM 1.5ft 3250/840 DALI M3hAt

8590515639120



- Degree of protection: IP20
- Impact strength: IK08
- Life time: 50000 hours
- System efficacy: 143 lm/W
- Colour rendering index CRI: 80-89, 4000–4000 K
- Chromaticity tolerance (initial MacAdam): SDCM3
- Protection class: I
- Flickering value Pst LM: 0,008
- Power factor: 0,95
- Stroboscope effect value SVM: 0,012
- Energy efficiency class of the light source: D

- Body: aluminium profile, white (RAL 9003)
- Diffuser: translucent polycarbonate (PC), UV stable, impact resistant
- Reflector: steel sheet, white (RAL 9003)
- Connection: 2x screwless, five-pole terminal block, three-phase interconnection
- Suspended indoor light fitting with accessories for various installation configurations either separately or in groups
- The light fitting does not include end caps, couplers or suspender. Must be ordered separately
- Opal diffuser made of highly permeable, translucent polycarbonate
- Digitally dimmable DALI driver (AC/DC), emergency back-up power supply with automated self-testing and 3 hour runtime
- Emergency back-up power supply for permanent and emergency lighting, connected to L3 (lum. flux 440lm)



| Code  | Type                              | Luminous flux of LED modules [lm] | Luminous flux of light fitting: [lm] | Power consumption: [W] | System efficacy: [lm/W] | Net weight: [kg] | A [mm] | D [mm] |
|-------|-----------------------------------|-----------------------------------|--------------------------------------|------------------------|-------------------------|------------------|--------|--------|
| 63912 | MO SLIM 1.5ft 3250/840 DALI M3hAt | 3240                              | 2790                                 | 19,5                   | 143                     | 3,7              | 1410   | 1410   |

The values stated for power consumption and luminous flux are in a tolerance of  $\pm 7.5\%$

FEATURES



CERTIFICATION



DOWNLOAD





**63912**

MO SLIM 1.5ft 3250/840 DALI M3hAt

8590515639120

