TREVOS


CODE | EAN


64353 | PRIMA LED 1.4ft SNS PC 3200/840 CORRIDOR 3F | 8590515643530




- Degree of protection: IP66
- Ambient temperature: -25—45 °C
- Impact strength: IK10
- Life time: 50000 hours
- System efficacy: 145 lm/W
- Colour rendering index CRI: 80-89, 4000—4000 K
- Chromaticity tolerance (initial MacAdam): SDCM3
- Cable glands: PG 13.5 thread
- Protection class: I
- Max. number of luminaires per circuit breaker B16: 21
- Max. number of luminaires per circuit breaker C16: 35
- Flickering value Pst LM: 1
- Power factor: 0,95
- Stroboscope effect value SVM: 0,4
- Total harmonic distortion: 10
- Energy efficiency class of the light source: D

- Body: grey PC (high mechanical resistance, UV stability, RAL 7035)
- Diffuser: translucent PC (high mechanical resistance, UV stability)
- Reflector: steel sheet, white (RAL 9003)
- Clips: polyamide + 15 % fibreglass
- Sealing: polyurethane (PUR), foam-filled base groove
- Connection: screwless five-pole terminal block, 5-wire connecting cabling for feed-through installation (1.5 mm2 cross-section, 2.5 mm2 available on demand)
- Light fitting with a built-in microwave sensor for height of 1-6 m, sensitivity of 2 - 50 lx and time interval of 5 sec to 30 min
- Optimal mounting height: 3 to 8 m
- Digitally dimmable DALI driver with corridor function, microwave motion sensor







Code	Type	Ta Max.: [°C]	Luminous flux of LED modules [lm]	Luminous flux of light fitting: [lm]	Power consumption: [W]	System efficacy: [lm/W]	Net weight: [kg]	A [mm]	D [mm]
64353	PRIMA LED 1.4ft SNS PC 3200/840 CORRIDOR 3F	45	3100	2760	19,1	145	1,9	1272	700

The values stated for power consumption and luminous flux are in a tolerance of ± 7.5 %

FEATURES

IP66 | up to Ta -25°C | up to Ta 45°C | 850°C | IK10 | LED | WARRANTY 5 | D | 220-240 V 50/60 Hz | DALI | 3F | CRI >80 | CCT 4000 K 3 SDCM | L90 B10

CERTIFICATION

CE | HACCP

DOWNLOAD

DATA SHEET | CE | HACCP | LDT DATA

TREVOS

CODE | EAN

64353 | PRIMA LED 1.4ft SNS PC 3200/840 CORRIDOR 3F | 8590515643530



















