TREVOS


CODE | EAN


74217 | CANOPUS NB TR 22000/840 DALI M1hAt | 8590515742172



- Degree of protection: IP65
- Ambient temperature: 0—35 °C
- Impact strength: IK10
- Life time: 50000 hours
- System efficacy: 154 lm/W
- Colour rendering index CRI: 80-89, 4000—4000 K
- Chromaticity tolerance (initial MacAdam): SDCM3
- Terminal block: connector, 0.4 m cable
- Protection class: I
- Max. number of luminaires per circuit breaker B16: 6
- Max. number of luminaires per circuit breaker C16: 11
- Power factor: 0,95
- Total harmonic distortion: 4
- Energy efficiency class of the light source: D

- Body: steel sheet, white (RAL 9003)
- Diffuser: clear heat-strengthened safety glass (TR)
- Reflector: parabolic polished aluminium spotlight with narrow beam (NB) angle
- Sealing: EPDM glued to the base of the light
- Connection: connector, 0.4 m cable
- Light fitting for industrial environments with no risk of explosion caused by gas, dust or flammable vapours, for installation onto tall ceilings
- Heat-strengthened safety glass with shatter pursuant to ČSN EN 12150-1
- Digitally dimmable DALI driver (AC/DC), emergency back-up power supply with automated self-testing and 1 hour runtime
- Emergency back-up power supply for permanent and emergency lighting, connected to L3 (lum. flux 440lm)





Code	Type	Luminous flux of LED modules [lm]	Luminous flux of light fitting: [lm]	Power consumption: [W]	System efficacy: [lm/W]	Net weight: [kg]
74217	CANOPUS NB TR 22000/840 DALI M1hAt	22450	19760	128,7	154	13,2

The values stated for power consumption and luminous flux are in a tolerance of ± 7.5 %

FEATURES

IP65 | up to 0°C | up to 35°C | 960°C | IK 10 | LED | D | 220-240 V 50/60 Hz | DALI | EMERGENCY | CRI >80 | CCT 4000 K 3 SDCM | L90 B50

DOWNLOAD

INSTALLATION MANUAL | DATA SHEET | LDT DATA

TREVOS

CODE | EAN

74217 | CANOPUS NB TR 22000/840 DALI M1hAt | 8590515742172









