



74238


CANOPUS NB TR 30000/840 DALI M3hAt

8590515742387



- Degree of protection: IP65
- Ambient temperature: 0–35 °C
- Impact strength: IK10
- Life time: 50000 hours
- System efficacy: 149 lm/W
- Colour rendering index CRI: 80-89, 4000–4000 K
- Chromaticity tolerance (initial MacAdam): SDCM3
- Terminal block: connector, 0.4 m cable
- Protection class: I
- Max. number of luminaires per circuit breaker B16: 18
- Max. number of luminaires per circuit breaker C16: 30
- Power factor: 0,97
- Total harmonic distortion: 6
- Energy efficiency class of the light source: D

- Body: steel sheet, white (RAL 9003)
- Diffuser: clear heat-strengthened safety glass (TR)
- Reflector: parabolic polished aluminium spotlight with narrow beam (NB) angle
- Sealing: EPDM glued to the base of the light
- Connection: connector, 0.4 m cable
- Light fitting for industrial environments with no risk of explosion caused by gas, dust or flammable vapours, for installation onto tall ceilings
- Heat-strengthened safety glass with shatter pursuant to ČSN EN 12150-1
- Digitally dimmable DALI driver (AC/DC), emergency back-up power supply with automated self-testing and 3 hour runtime
- Emergency back-up power supply for permanent and emergency lighting, connected to L3 (lum. flux 440lm)



| Code  | Type                                  | Luminous flux of LED modules<br>[lm] | Luminous flux of light fitting:<br>[lm] | Power consumption:<br>[W] | System efficacy:<br>[lm/W] | Net weight:<br>[kg] |
|-------|---------------------------------------|--------------------------------------|-----------------------------------------|---------------------------|----------------------------|---------------------|
| 74238 | CANOPUS NB TR 30000/840 DALI<br>M3hAt | 31360                                | 27600                                   | 184,7                     | 149                        | 13,4                |

The values stated for power consumption and luminous flux are in a tolerance of  $\pm 7.5\%$

FEATURES



DOWNLOAD



