TREVOS

CODE

77693

FUTURA 2.5ft ABSc Al 11000/840 DALI 3F


EAN


8590515776931




- Degree of protection: IP66
- Ambient temperature: -25—45 °C
- Impact strength: IK06
- Life time: 150000 hours / L95 @25°C
- System efficacy: 153 lm/W
- Colour rendering index CRI: 80-89, 4000—4000 K
- Chromaticity tolerance (initial MacAdam): SDCM3
- Cable glands: M20x1.5 thread
- Protection class: I
- Max. number of luminaires per circuit breaker B16: 15
- Max. number of luminaires per circuit breaker C16: 25
- Energy efficiency class of the light source: C

- Body: Dark grey ABS (high chemical resistance, UV stability, RAL 7001)
- Diffuser: Translucent acrylic (AC), UV stable, chemically resistant
- Reflector: Steel sheet, white (RAL 9003)
- Clips: Stainless steel + polyamide
- Sealing: Polyurethane (PUR), foam-filled base groove
- Connection: Screwless seven-pole terminal block, 7-wire connecting cabling for feed-through installation (1.5 mm2 cross-section, 2.5 mm2 available on demand)
- Unique design, resistant against humidity and dust, with IP66 enclosure rating and built-in aluminium heat sinks
- Optimal mounting height: 3.5 to 10 m
- Digitally dimmable DALI driver (AC/DC)







Code	Type	Ta Max.: [°C]	Luminous flux of LED modules [lm]	Luminous flux of light fitting: [lm]	Power consumption: [W]	System efficacy: [lm/W]	Net weight: [kg]	A [mm]	D [mm]
77693	FUTURA 2.5ft ABSc Al 11000/840 DALI 3F	45	11260	9910	64,7	153	3,2	1452	940

The values stated for power consumption and luminous flux are in a tolerance of ± 7.5 %

FEATURES

IP66 · up to t_a -25°C · up to t_a 45°C · 650°C · IK 06 · LED · WARRANTY 5 · D · 220-240 V 50/60 Hz · DALI · 3F · CRI >80 · CCT 4000 K 3 SDCM · L95 @25°C

CERTIFICATION

CE · CB test · HACCP

DOWNLOAD

INSTALLATION MANUAL · DATA SHEET · CE · ENEC · CB · HACCP · LDT DATA

TREVOS

CODE | EAN

77693 | FUTURA 2.5ft ABSc Al 11000/840 DALI 3F | 8590515776931



