TREVOS


CODE | EAN


79053 | FUTURA 2.4ft SNS PC Al 6400/840 CORRIDOR | 8590515790531




- Degree of protection: IP66
- Ambient temperature: -25—50 °C
- Impact strength: IK10
- Life time: 50000 hours
- System efficacy: 162 lm/W
- Colour rendering index CRI: 80-89, 4000—4000 K
- Chromaticity tolerance (initial MacAdam): SDCM3
- Cable glands: PG 13.5 thread
- Protection class: I
- Max. number of luminaires per circuit breaker B16: 21
- Max. number of luminaires per circuit breaker C16: 35
- Flickering value Pst LM: 0,076
- Power factor: 0,95
- Stroboscope effect value SVM: 0,022
- Total harmonic distortion: 15
- Energy efficiency class of the light source: D

- Body: grey PC (high mechanical resistance, UV stability, RAL 7035)
- Diffuser: translucent PC (high mechanical resistance, UV stability)
- Reflector: steel sheet, white (RAL 9003)
- Clips: polyamide + 15 % fibreglass
- Sealing: polyurethane (PUR), foam-filled base groove
- Connection: screwless three-pole terminal block
- Unique design, resistant against humidity and dust, with IP66 enclosure rating and built-in aluminium heat sinks
- Optimal mounting height: 3.5 to 10 m
- Digitally dimmable DALI driver with corridor function, microwave motion sensor







Code	Type	Ta Max.: [°C]	Luminous flux of LED modules [lm]	Luminous flux of light fitting: [lm]	Power consumption: [W]	System efficacy: [lm/W]	Net weight: [kg]	A [mm]	D [mm]
79053	FUTURA 2.4ft SNS PC Al 6400/840 CORRIDOR	50	6240	5870	36,3	162	2,9	1172	700

The values stated for power consumption and luminous flux are in a tolerance of ± 7.5 %

FEATURES



DOWNLOAD

DATA SHEET LDT DATA

TREVOS

CODE | EAN

79053 | FUTURA 2.4ft SNS PC Al 6400/840 CORRIDOR | 8590515790531

