TREVOS


CODE | EAN


79815 | FUTURA 2.5ft MAX PCc Al 11000/840 DALI | 8590515798155




- Degree of protection: IP66
- Ambient temperature: -40—60 °C
- Impact strength: IK10
- Life time: 150000 hours / L95 @25°C
- System efficacy: 161 lm/W
- Colour rendering index CRI: 80-89, 4000—4000 K
- Chromaticity tolerance (initial MacAdam): SDCM3
- Cable glands: M20x1.5 thread
- Protection class: I
- Max. number of luminaires per circuit breaker B16: 18
- Max. number of luminaires per circuit breaker C16: 30
- Flickering value Pst LM: 1
- Power factor: 0,95
- Stroboscope effect value SVM: 0,4
- Total harmonic distortion: 8
- Energy efficiency class of the light source: C

- Body: Grey PC (high mechanical resistance, UV stability, RAL 7035)
- Diffuser: Translucent PC (high mechanical resistance, UV stability)
- Reflector: Steel sheet, white (RAL 9003)
- Clips: Stainless steel + polyamide
- Sealing: Polyurethane (PUR), foam-filled base groove
- Connection: Screwless five-pole terminal block
- Unique design, resistant against humidity and dust, with IP66 enclosure rating and built-in aluminium heat sinks
- Optimal mounting height: 3.5 to 10 m
- Digitally dimmable DALI driver (AC/DC)
- Light fitting for environments with high ambient temperature







Code	Type	Ta Max.: [°C]	Luminous flux of LED modules [lm]	Luminous flux of light fitting: [lm]	Power consumption: [W]	System efficacy: [lm/W]	Net weight: [kg]	A [mm]	D [mm]
79815	FUTURA 2.5ft MAX PCc Al 11000/840 DALI	60	11160	10490	65,1	161	3,2	1452	940

The values stated for power consumption and luminous flux are in a tolerance of ± 7.5 %

FEATURES



CERTIFICATION



DOWNLOAD

INSTALLATION MANUAL | DATA SHEET | CE | CB | HACCP | LDT DATA

TREVOS

CODE | EAN

79815 | FUTURA 2.5ft MAX PCc Al 11000/840 DALI | 8590515798155











