TREVOS


CODE | EAN


86800 | PERUN SLIM 1.5ft 5500/840 | 8590515868001



- Degree of protection: IP65
- Ambient temperature: -25—35 °C
- Impact strength: IK10
- Life time: 50000 hours
- System efficacy: 134 lm/W
- Colour rendering index CRI: 80-89, 4000—4000 K
- Chromaticity tolerance (initial MacAdam): SDCM3
- Cable glands: PG 13.5 thread, brass with surface finish
- Protection class: I
- Max. number of luminaires per circuit breaker B16: 16
- Max. number of luminaires per circuit breaker C16: 27
- Flickering value Pst LM: 0,076
- Power factor: 0,95
- Stroboscope effect value SVM: 0,022
- Total harmonic distortion: 15
- Energy efficiency class of the light source: D

- Body: steel sheet, impact resistant, chemically resistant
- Diffuser: satin, heat-strengthened safety glass
- Reflector: steel sheet, white (RAL 9003)
- Clips: stainless steel
- Sealing: silicone, on the base of the light
- Connection: screwless three-pole terminal block
- Light fitting with high chemical and mechanical resistance designed for use in environments with no risk of explosion caused by gas, dust or flammable vapours
- The base is made of austenitic stainless steel 1.4301 / AISI 304 with high corrosion resistance.
- Heat-strengthened safety glass with shatter pursuant to ČSN EN 12150-1
- ON/OFF electronic driver (AC, DC on demand)





Code	Type	Luminous flux of LED modules [lm]	Luminous flux of light fitting: [lm]	Power consumption: [W]	System efficacy: [lm/W]	Net weight: [kg]	A [mm]	D [mm]
86800	PERUN SLIM 1.5ft 5500/840	5340	4270	31,9	134	5,3	1600	1050

The values stated for power consumption and luminous flux are in a tolerance of ± 7.5 %

FEATURES

IP65 | up to -25°C | up to 35°C | 960°C | IK10 | LED | WARRANTY 5 | D | 220-240 V 50/60 Hz | CRI >80 | CCT 4000 K 3 SDCM | L90 B10

CERTIFICATION

CE

DOWNLOAD

INSTALLATION MANUAL | DATA SHEET | CE | LDT DATA

TREVOS

CODE | EAN

86800 | PERUN SLIM 1.5ft 5500/840 | 8590515868001

