TREVOS


CODE | EAN


**88363** | PRIMA LED 1.4ft TRS PCc 2600/840 DALI 3F | 8590515883639




- Degree of protection: IP66
- Ambient temperature: -25—45 °C
- Impact strength: IK10
- Life time: 50000 hours
- System efficacy: 143 lm/W
- Colour rendering index CRI: 80-89, 4000—4000 K
- Chromaticity tolerance (initial MacAdam): SDCM3
- Cable glands: PG 13.5 thread
- Protection class: I
- Max. number of luminaires per circuit breaker B16: 21
- Max. number of luminaires per circuit breaker C16: 35
- Flickering value Pst LM: 1
- Power factor: 0,95
- Stroboscope effect value SVM: 0,4
- Total harmonic distortion: 10
- Energy efficiency class of the light source: D

- Body: clear PC (high mechanical resistance, UV stability)
- Diffuser: clear PC (high mechanical resistance, UV stability)
- Reflector: steel sheet, white (RAL 9003), modified for indirect lighting
- Clips: stainless steel + polyamide
- Sealing: polyurethane (PUR), foam-filled base groove
- Connection: screwless seven-pole terminal block, 7-wire connecting cabling for feed-through installation (1.5 mm2 cross-section, 2.5 mm2 available on demand)
- Light fitting with a clear base, suitable for direct and indirect lighting of spaces with low clear height
- Optimal mounting height: 3 to 8 m
- Digitally dimmable DALI driver (AC/DC)




| Code | Type | Ta Max.: [°C] | Luminous flux of LED modules [lm] | Luminous flux of light fitting: [lm] | Power consumption: [W] | System efficacy: [lm/W] | Net weight: [kg] | A [mm] | D [mm] |
|---|---|---|---|---|---|---|---|---|---|
| 88363 | PRIMA LED 1.4ft TRS PCc 2600/840 DALI 3F | 45 | 2600 | 2310 | 16,1 | 143 | 1,9 | 1272 | 700 |

The values stated for power consumption and luminous flux are in a tolerance of ± 7.5 %

FEATURES

IP66 | up to Ta -25°C | up to Ta 45°C | 850°C | IK 10 | LED | WARRANTY 5 | D | 220-240 V 50/60 Hz | DALI | 3F | CRI >80 | CCT 4000 K 3 SDCM | L90 B10

CERTIFICATION

CE | CB test | HACCP

DOWNLOAD

INSTALLATION MANUAL | DATA SHEET | CE | ENEC | CB | HACCP | LDT DATA

TREVOS

CODE

EAN

**88363** | PRIMA LED 1.4ft TRS PCc 2600/840 DALI 3F | 8590515883639



