TREVOS


CODE | EAN


**95720** | NAOS SQUARE 6400/840 ML | 8590515957200




- Degree of protection: IP40
- Ambient temperature: -25—35 °C
- Impact strength: IK02
- Life time: 150000 hours / L95 @25°C
- System efficacy: 141 lm/W
- Colour rendering index CRI: 80-89, 4000—4000 K
- Chromaticity tolerance (initial MacAdam): SDCM3
- Cable glands: rubber
- Protection class: I
- Max. number of luminaires per circuit breaker B16: 25
- Max. number of luminaires per circuit breaker C16: 38
- Flickering value Pst LM: 0,076
- Power factor: 0,95
- Stroboscope effect value SVM: 0,022
- Total harmonic distortion: 15
- Energy efficiency class of the light source: C

- Body: Steel sheet, white (RAL 9003)
- Diffuser: Acrylic (PMMA), sandblasted from both sides
- Connection: Screwless five-pole terminal block
- Modern, low-profile light fitting for indoor lighting in offices, corridors and common rooms
- Opal diffuser made of highly permeable, translucent PMMA
- ON/OFF electronic driver (AC, DC on demand)




| Code | Type | Luminous flux of LED modules [lm] | Luminous flux of light fitting: [lm] | Power consumption: [W] | System efficacy: [lm/W] | Net weight: [kg] |
|---|---|---|---|---|---|---|
| 95720 | NAOS SQUARE 6400/840 ML | 6520 | 5410 | 38,4 | 141 | 5,7 |

The values stated for power consumption and luminous flux are in a tolerance of ± 7.5 %

FEATURES

IP40 | up to ta -25°C | up to ta 35°C | 850°C | LED | WARRANTY 5 | D | 220-240 V 50/60 Hz | CRI >80 | CCT 4000 K 3 SDCM | L95 @25°C

CERTIFICATION

CE

DOWNLOAD

INSTALLATION MANUAL | DATA SHEET | CE | LDT DATA